



AimLite

SDH-L DUAL HEAD LED SECURITY LIGHT

3 CCT SELECTABLE



FEATURES

- 20W (1 974 lumens)
- 3 CCT Selectable (3 000/4 000/5 000 K)
- Bronze or white finish
- Frosted glass lens
- Integrated motion sensor and dusk-till-dawn photocell
- Always ON mode available



PART NO	WATTS	VOLTS	COLOR TEMP.	LUMEN OUTPUT	EFFICACY	CRI	LIFE L70	TESTED HOURS LM-80	CALC. TM21	BEAM ANGLE	BUG	LED CURRENT	FINISH	DIM- MING	PF	THD	TRADITIONAL EQUIVALENT		MAS- TER CASE QTY
	[W]	[VAC]	[K] ¹	[LM] ^{2,3}	[LM/W]		[HRS] ⁴	[HRS] ⁴	[HRS] ⁴	[°]		[MA]					[W]		
																	MH	HPS	
	CCT SELECTABLE																		
SDH-LA1B-4-3C-BR	20	120	3 000/4 000/5 000	1 974	96 - 99	80+	>100 000	10 000	>60 000	50	B2-U1-G0	0.18	Bronze	No	>0.9	<20	2x100	2x60-75	5
SDH-LA1B-4-3C-WH	20	120	3 000/4 000/5 000	1 974	96 - 99	80+	>100 000	10 000	>60 000	50	B2-U1-G0	0.18	White	No	>0.9	<20	2x100	2x60-75	5

¹ Typical color temperature range: +/- 5 %.

² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

³ Lumen values are based on 4 000 K default programming. Please refer to the LUMEN SPECIFICATION TABLE for more details on other color temperatures.

⁴ Life hours are derived from IESNA LM-80-08 testing report and projected per IESNA TM-21-11 extrapolations.

Physical Characteristics

