

AimLite

W6C LED FULL CUT-OFF WALL PACK

SELECTABLE COLOR TEMPERATURE (3 000/4 000/5 000 K), POWER SELECTABLE, INTEGRATED PHOTOCELL AND MULTI-VOLTAGE (120-347 V)



FEATURES

- Power selectable: 25/40/60 W and 80/100 W
- 3 CCT select: 3 000/4 000/5 000 K
- Integrated Photocell that can be easily disabled
- 0-10 V dimmable
- 4 conduit entries of 1/2" on each side
- Clear Polycarbonate lens
- 120-347 V
- Ambient temperature: -40°C to +50°C
- Accessory: Back plate



MODEL NUMBER	WATTS [W]	VOLTS [VAC]	COLOR TEMP. [K]	LUMEN OUTPUT [LM]	EFFICIENCY [LM/W]	CRI	LIFE L70 [HRS]	DIS-TRIB. TYPE	FINISH	DIM-MING	PF	THD [%]	TRADITIONAL EQUIVALENT [W]		CASE QTY [MASTER]
													HM	SHP	
W6C-PS60A3-323CBRP	25/40/60	120-347	3 000/ 4 000/ 5 000	3 625/ 5 640/ 8 220 ¹	122-137	80	50 000	III	BRONZE	YES	≥0.9	≤20%	175-400	175-250	1
W6C-PS100A323C3BRP	80/100	120-347	3 000/ 4 000/ 5 000	11 520/ 14 000 ¹	123-140	80	50 000	III	BRONZE	YES	≥0.9	≤20%	400-1 000	250-400	1



¹ DEFAULT PROGRAMMING 4 000 K.

DATA IS BASED UPON TESTS PERFORMED IN A CONTROLLED ENVIRONMENT. ACTUAL PERFORMANCE CAN VARY DEPENDING ON OPERATING CONDITIONS. ALL PRODUCTS ARE SUBJECT TO CHANGE OR MAY BE DISCONTINUED ANY TIME WITHOUT NOTICE.

AimLite

W6C

T 514 227-1288

TF 1866 348-2374

aimlite.com