

AimLite

UCL UNDER CANOPY AND GARAGE LIGHT

3 POWER SELECTABLE AND 3 CCT SELECTABLE,
CONTROL-READY



FEATURES

- Power selection (40/60/70 W), delivering up to 9 062 lumens
- 3 CCT Selectable (3 000/4 000/5 000 K), default setting at 4 000 K
- Control-Ready with a pre-installed receptacle (compatible with smart and non-smart sensors)
- Integrated On/Off photocell
- 120-347 V



AimLite

UCL

T 514 227-1288

TF 1866 348-2374

aimlite.com

PART NUMBER	WATTS	VOLTS	COLOR TEMP.	LUMEN OUTPUT	EFFI- CACY	CRI	LIFE L70	TESTED HOURS LM-80	CALC. TM21	LED CURRENT	FINISH	DIM- MING	PF	THD	BUG	TRADITIONAL EQUIVALENT		MASTER CASE QTY	
	[W]	[VAC]	[K] ¹	[LM] ^{2,3}	[LM/W]		[HRS] ⁴	[HRS] ⁴	[HRS] ⁴	[MA]		[YES/ NO]		[%]		[W]			
																	MH		HPS
CCT AND POWER SELECTABLE WITH INTEGRATED PHOTOCELL ⁴																			
UCL-PS70A-32-3C8RP	40/60/70	120-347	3 000/4 000/5 000	6 022-9 062	141-146	80+	50 000	9 000	>36 000	344.9-557.8	Bronze	Yes	>0.9	<20%	B3-U3-G2	100-175	100-175	4	
UCL-PS70A-32-3CWHP	40/60/70	120-347	3 000/4 000/5 000	6 022-9 062	141-146	80+	50 000	9 000	>36 000	344.9-557.8	White	Yes	>0.9	<20%	B3-U3-G2	100-175	100-175	4	

¹ Typical color temperature range: +/- 5 %.

² Lumen values are based on 4 000 K default programming. Please refer to the LUMEN SPECIFICATION TABLE for more details on other color temperatures.

³ Life hours are derived from IESNA LM-80-08 testing report and projected per IESNA TM-21-11 extrapolations.

⁴ Integrated ON/OFF photocell that can be easily enabled.

Physical Characteristics

- CCT and Power select switches

- Side entry for conduit mounting

- Frosted Polycarbonate lens


- Receptacle included to allow for smart or non-smart sensors

- 120-347V photocell




Standard Mounting Offering

Surface Mount



Pendant mount (pipe not supplied)



Conduit mount

