




Series Spec Sheet

LOW VOLTAGE LED TAPE

4.4 W, 24 V - IP22

Stanpro's Low Voltage Tape Systems allow the customization of any area, combining style and technology with reliability. This professional grade flexible LED tape is ideal for installations that require a high degree of quality, a broad variety of key features, and limitless application possibilities such as stairway, cabinetry, coves, shelving, and linear decorative lighting.

View our full collection of LED strip tapes and extrusion offerings in our [brochure](#).

FEATURES AND SPECIFICATIONS

• Construction

Physical Characteristics

- Reel length 16.4' (5 m)
- 54.9 LED/ft, 180 LED/m, 900 LED/reel
- Can be cut every 1 5/16" (6 LED)
- Field cuttable

Mounting

- 3M Adhesive backing for an easy installation to smooth surfaces
- Mounting is available with [extrusion](#) for recessed, surface or suspended installation.
- Solderless option is available with a wide choice of connectors and accessories.
- 24 V plug-in or hardwired remote drivers

• Performance data

- Available color temperatures: 3 000 and 4 000 K
- Total reel wattage 73 W
- 90+ CRI
- DC, Constant voltage
- Estimated lifespan of 50 000 hours to L70
- Forward and reverse phase, optional dimming with dimmable driver
- Ambient temperature: -25 °C to 40 °C
- Suitable for dry location

3
yrs
warranty


dimmable


dry
location



OVERVIEW

Light source	LED
Watts (W)	4.4
Lumen output (lm)	300 and 314
Efficacy (lm/W)	68 and 71
Color temperature (K)	3 000 and 4 000
CRI	90+

QUICK SHIP AND TECHNICAL SPECIFICATION TABLE


LOW VOLTAGE LED TAPE

Order code	Model number	Watts (W) (per ft.) (per m.)		Volts (V DC)	Color temp. (K) ¹	Lumen output (lm) ² (per ft.) (per m.)		Efficacy (lm/W)	CRI	Life L70 (hrs) ³	Power factor	Master case qty
Reel 16.4' (5m)												
65889 ⁴	TAPE/16.4'/4.4W/30K/24V/IP22/180/8MM/STD	4.4	14.5	24	3 000	300	984	68	90+	50 000	>0.9	25
65890 ⁴	TAPE/16.4'/4.4W/40K/24V/IP22/180/8MM/STD	4.4	14.5	24	4 000	314	1 030	71	90+	50 000	>0.9	25

¹ Typical color temperature range: +/- 5 %.² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.³ Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 extrapolations.⁴ The LED tape reels are not returnable if already cut.**LED DRIVERS AND DIMMER SWITCH (order separately)**

Order code	Model number	Output power (W)	input volts (VAC)	Input Current (mA)	Frequency (Hz)	IP rating	Master case qty
24 V DC							
Hardwired - Dimmable							
70511	LED/DRIVER/30W/24V/HW/5-IN-1D	30	100-277	500	47/63	-	20
70512	LED/DRIVER/60W/24V/HW/5-IN-1D	60	100-277	800	47/63	-	10
65742	LED/DRIVER/96W/24V/HW/D/STD	96	100-130	800	50/60	IP66	10
70513	LED/DRIVER/96W/24V/HW/5-IN-1D	96	100-277	1 100	47/63	-	10
69132	LED/DRIVER/192W/24V/HW/D	192 (2 x 96)	120-277	2 200	47/63	-	10
69133	LED/DRIVER/288W/24V/HW/D	288 (3 x 96)	120-277	3 100	47/63	-	10
Plug-in - Non-dimmable							
65750	LED/DRIVER/60W/24V/PLUG/ND/STD	60	100-240	1 500	50/60	IP20	36
69554	LED/DRIVER/36W/24V/PLUG/ND	36	100-240	1 500	50/60	IP20	50


Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions.
All products are subject to change or may be discontinued any time without notice.

QUICK SHIP AND TECHNICAL SPECIFICATION TABLE 

Order code	Model number	Description	Figure	Dimensions	Compatible	Colour	Certification	Qty per pack	Master case qty
66130	TAPE/8MM/SINGLE_END_CONN/STD	Tape to Wire (8 mm)	A	2 m. wire (incl.)	20-22 AWG TR64 type	Clear / Black	RoHS	10	300
66132	TAPE/8MM/IN_LINE_CONN/STD	Tape to Tape (8mm)	A	-	LV LED Tapes (8mm)	Clear / Black	RoHS	10	300
66239	TAPE/WIRE_TO_WIRE_CONN/STD	Wire to Wire (8mm)	B	-	20-22 AWG TR64 type	Clear / Black	-	10	300
66771	TAPE/2WAY_WIRE_TO_WIRE_CONN/STD	Two way - Wire to Wire	C	11.2 x 13.1 x 8.3 mm	12-24 AWG	Orange	-	1	100
66242	TAPE/5WAY_WIRE_TO_WIRE_CONN/STD 4P	Five way - Wire to Wire	D	18.6 x 29.9 x 8.3 mm	12-24 AWG	Orange	-	5	200
66240	TAPE/WIRE_TO_DC_FEMALE/STD	Wire to DC Female	E	12"	20 AWG	Black	-	1	50
66241	TAPE/WIRE_TO_DC_MALE/STD	Wire to DC Male	F	12"	20 AWG	Black	-	1	50
66243	TAPE/DOUBLE_FACE_33M/STD	Double face tape	G	33 m	-	Red	-	1	10
67630	TAPE/8MM/LSHAPECORNER/STD 5P	L Shape PCB Joiner	H	20 x 8 mm	-	White	RU	1	250
67631	TAPE/8MM/TSHAPECORNER/STD 5P	T Shape PCB Joiner	I	32 x 20x 8 mm	-	White	RU	1	250
69734	TAPE/1 TO 5 ENTRY_DC_SPLITTER_FEMALE	Five way wire to DC Female	J	11 x 11 x 400 mm	-	Black	-	1	250

DIMENSIONS

24 V - 4.4 W/ft. (14.5 W/m)




Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions.
All products are subject to change or may be discontinued any time without notice.

PHOTOMETRIC DATA¹

65889 • TAPE/16.4'/4.4W/30K/24V/IP22/180/8MM/STD • 3 000 K • 287.0 lm

Polar candela distribution



Zonal lumen summary

Zone	Lumens	% Fixture
0-30	76.7	26.7
0-40	126.7	44.1
0-60	227.8	79.4
60-90	59.2	20.6
0-90	287.0	100


Illuminance at a distance

Center beam fc		Beam width	
1.7'	33.8	5.4'	5.6'
3.3'	8.98	10.5'	10.8'
5.0'	3.91	15.9'	16.3'
6.7'	2.18	21.4'	21.9'
8.3'	1.42	26.5'	27.1'
10.0'	0.98	31.9'	32.7'

Vert. spread: 115.8°
 Horiz. spread: 117.1°

65890 • TAPE/16.4'/4.4W/40K/24V/IP22/180/8MM/STD • 4 000 K • 287.0 lm

Polar candela distribution



Zonal lumen summary

Zone	Lumens	% Fixture
0-30	76.7	26.7
0-40	126.7	44.1
0-60	227.8	79.4
60-90	59.2	20.6
0-90	287.0	100

Illuminance at a distance

Center beam fc		Beam width	
1.7'	33.8	5.4'	5.6'
3.3'	8.98	10.5'	10.8'
5.0'	3.91	15.9'	16.3'
6.7'	2.18	21.4'	21.9'
8.3'	1.42	26.5'	27.1'
10.0'	0.98	31.9'	32.7'

Vert. spread: 115.8°
 Horiz. spread: 117.1°

¹ Complete IES files available on our website.

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions.
 All products are subject to change or may be discontinued any time without notice.