

Project: _

Drawn by:

_____ Catalogue #: ____

Type:

Date: _

Series Spec Sheet

L2SSQ LED SLIM STRIP WITH SQUARE LENS 3 CCT Selectable

The L2SSQ series showcases a slim profile, allowing for installation in tight and restrictive spaces. Benefit from high-performance light output without sacrificing smooth and uniform lighting. With its sleek and modern square lens design, the L2SSQ series is the ideal choice for commercial, industrial, and retail applications.

FEATURES AND SPECIFICATIONS

• Construction

Physical Characteristics

- Sleek and compact design ideal for installation in tight spaces
- 24 gauge semi-gloss white powder painted steel
 Frosted PMMA lens
- CCT Selectable switch placed discretely inside the housing

Mounting

- Surface, suspended or row mounted (see accessories)
- Canopy plate for octagonal junction box and mounting brackets are included

• Performance Data

- Available in 3 500/4 000/5 000 K selectable color temperature
- 80+ CRI
- Electrical ratings: 120-347 V
- Estimated life of over 186 000 hours to L70
- 0-10 V dimming standard
- 2.5 kV surge protection
- Operating temperature:
- -20 °C to 50 °C (-4 °F to 122 °F)

OVERVIEW

Light source	LED
Watts (W)	45, 90
Lumen output (Im)	5 985, 11 970
Efficacy (Im/W)	133
Color temperature (K)	3 500/4 000/5 000
CRI	80+

• Compliances

- UL listed for Canada and USA for damp locations
- DLC Premium and Standard
- Meets requirements of ICES-005 issue 5 class A for use in commercial applications



· r ·

Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/search.





OUICK SHIP AND TECHNICAL SPECIFICATION TABLE

Order code	Model number	Watts (W)	Volts (V AC)	Color temp. (K) ¹	Lumen output (Im) ²	Efficacy (Im/W)	CRI	Life L70 (hrs) ³	Tested hours LM-80 (hrs) ³	Dimming (Yes/No)	Power factor	THD (%)	Case qty (master)
48"							1 1						
69046	5 L2SSQ-48LS2-Q/3C	45	120-347	3 500/4 000/5 000	5 985	133	80+	186 000	9 000	Yes	0.90	10	9
96"													
69047	7 2SSQ-96 S2-Q/3C	90	120-347	3 500/4 000/5 000	11 970	133	80+	186 000	9 000	Yes	0.90	10	1

¹ Typical color temperature range: +/- 5 %.

² Lumen values are derived from DLC reported data at 3 500 K. Please refer to the LUMEN SPECIFICATION TABLE for more details on other color temperatures. ³ Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 extrapolations.

DLC UNIQUE ID TABLE

Order	Model Number	DLC Premium Unique ID	DLC Standard Unique ID
code		Stairwell	Linear Ambient
69046	L2SSQ-48LS2-Q/3C	S-8W6I50	S-PEV6AJ
69047	L2SSQ-96LS2-Q/3C	S-3WCLUR	S-YEOSKQ

LUMEN SPECIFICATION TABLE

Order	Model number	3 500 K		4 000	К	5 000 K	
code		Lumen output (Im)	Efficacy (Im/W)	Lumen output (Im)	Efficacy (Im/W)	Lumen output (Im)	Efficacy (Im/W)
69046	L2SSQ-48LS2-Q/3C	5 985	133	6 030	134	6 075	135
69047	L2SSQ-96LS2-Q/3C	11 970	133	12 060	134	12 150	135

DEFAULT PROGRAMMING

69046: 4 000 K

69047: 4 000 K

ACCESSORIES (order separately)

Туре
V-Hooks (set of 2)
Suspension kit - 2 chains (1 m) ¹
10' Aviation cable kit with canopy, power cord & dimming wires
Continuous row mounting connector
External mount PIR motion sensor (120-277 V only)
Remote control for PIR motion sensor
Wire guard kit 48"
Wire guard kit 96"
Replacement lens 48"
Replacement lens 96"

¹Must be used in conjunction with 69328.

COMPATIBLE DIMMERS¹

Brand	Model
Leviton	IllumaTech IP710-LFZ
	IllumaTech IP710-DLZ
	IllumaTech IP710-D0Z
	Decora DS710-10Z
Lutron	Nova T NTSTV-DV
	Nova NFTV
	Diva DVTV-WH
Legrand	RH4FBL3PW

Dimming range: 10%-100%

¹This table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Some dimmers may require more than one product for stable operation. Stanpro recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation.

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

INCLUDED IN THE BOX





Mounting Brackets

Canopy Plate for Octagonal Junction Box





DIMENSIONS AND WEIGHTS





PHOTOMETRIC DATA¹

69046 • L2SSQ-48LS2-Q/3C • 4 000 K • 6 025.1 Im

Polar candela distribution



Zonal lumen summary

Zone	Lumens	% Fixture
0-30	1 375.2	22.8
0-40	2 244.6	37.3
0-60	3 984.4	66.1
60-90	1 524.1	25.3
70-100	1 056.1	17.5
90-120	424.2	7
0-90	5 508.5	91.4
90-180	516.6	8.6
0-180	6 025.1	100

Illuminance at a distance



69047 • L2SSQ-96LS2-Q/3C • 4 000 K • 12 050.3 Im

Polar candela distribution



Zonal lumen summary

Zone	Lumens	% Fixture
0-30	2 750.3	22.8
0-40	4 489,2	37.3
0-60	7 968.9	66.1
60-90	3 048.1	25.3
70-100	2 112.1	17.5
90-120	848.5	7
0-90	11 017.0	91.4
90-180	1 033.3	8.6
0-180	12 050.3	100

Illuminance at a distance



¹ Complete IES files available on our website.

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

