



# LED Filament High Intensity



| Order code | Description                          | Watts<br>(W) | Base | Volts<br>(VAC) | Color temp.<br>(K) | CRI | Beam angle<br>(°) | Life<br>L70<br>(hrs) | Lumen output<br>(lm) | Case qty<br>(master) |
|------------|--------------------------------------|--------------|------|----------------|--------------------|-----|-------------------|----------------------|----------------------|----------------------|
| 70174      | ED23.5/20W/30K/BYP/E26/V/FIL/ND/STD  | 20           | E26  | 120-277        | 3 000              | 80  | Universal         | 25 000               | 3 500                | 12                   |
| 70175      | ED23.5/20W/40K/BYP/E26/V/FIL/ND/STD  | 20           | E26  | 120-277        | 4 000              | 80  | Universal         | 25 000               | 3 500                | 12                   |
| 69598      | ED23.5/20W/40K/BYP/EX39/V/FIL/ND/STD | 20           | EX39 | 120-277        | 4 000              | 80  | Universal         | 25 000               | 3 500                | 12                   |
| 69599      | ED28/40W/40K/BYP/EX39/V/FIL/ND/STD   | 40           | EX39 | 120-277        | 4 000              | 80  | Universal         | 25 000               | 7 500                | 12                   |
| 69600      | ED37/65W/40K/BYP/EX39/V/FIL/ND/STD   | 65           | EX39 | 120-277        | 4 000              | 80  | Universal         | 25 000               | 12 000               | 6                    |

## Traditional Equivalent

| LED  | CFL          | Incandescent  | HID           |
|------|--------------|---------------|---------------|
| 20 W | 40 W - 45 W  | 150 W - 200 W | 70 W - 100 W  |
| 40 W | 85 W - 105 W | 500 W         | 150 W - 200 W |
| 65 W | -            | -             | 400 W         |

Lumen values are derived from photometric testing

66  
wet  
location

enclosed  
fixture

non  
dimmmable

3  
yrs  
warranty

ETL  
Intertek