

Project: _

Drawn by:

_____ Catalogue #: ____

Type: _

Date: _

SLG-5L PLASTIC COMPACT BATTERY UNIT (Over 90 minutes Duration Standalone Unit) 2 x 5 W Crisp White LED Heads

The commercial SLG-5L features a plastic battery unit designed to provide an economical and versatile solution to emergency lighting needs within a small and compact design. The SLG-5L series is configured with two 5 W LED heads and can run for 90 minutes duration as a standalone unit.

FEATURES AND SPECIFICATIONS

• Circuitry

- 120/347V AC 60Hz Input, field selectable
- Solid state variable rate charger
- Over 90 minutes Duration Standalone Unit
- Momentary push button test switch
- Pilot LED for AC ON and CHARGE status
- Fully automatic, current limited charger
- Short circuit protection
- Complete battery recharge in 24 hours
- Maintenance free, sealed lead acid battery

- Mechanical
 - High impact, UV stabilized, thermoplastic construction
 - 2 x 5 W Crisp White LED Heads
 - Low profile, canopy type design with extremely small total footprint
 - Universal spider knockout pattern and keyhole mounting slots stamped into back of cabinet
 - Unit "quick snaps" onto backplate for simple, speedy installation
 - White color is standard

Note: Not intended for flush ceiling mount.

- Approval
- CSA Certified to C22.2 #141-15
- Compliance
 - Meets requirements of ICES-005

OVERVIEW

Linktonung	I ED
Light source	LED
Input voltage (V AC)	120 / 347
Emergency duration	Over 90 minutes







For complete warranty details, please see our terms and conditions on our website.





TECHNICAL SPECIFICATION TABLE

Part number	Volts	Watts	Nbr of heads	Head	Lamp	Light source	Input Volts	Color
	(V DC)	(W)			(W)		(VAC)	
SLG-5L	6	N/A	2	Ν	5	LED	120/347	White

ORDERING GUIDE


	SLG-5L	
	Series	
SLG-5L		

WIREGUARD²

Part number	Dimensions (in)
WGD630-V2	15.25 x 12.25 x 9.00

 $^{\rm 2}$ Please contact your Stanpro customer service representative for more information.

DIMENSIONS



Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

