

# General Service

| Order code                                           | Description                | Watts<br>(W) | Base | Volts<br>(V) | Lumens<br>at 120 V<br>(lm) | Average<br>life<br>(hrs) | Filament<br>type | Finish/<br>Color | Case<br>qty<br>(inner/master) |
|------------------------------------------------------|----------------------------|--------------|------|--------------|----------------------------|--------------------------|------------------|------------------|-------------------------------|
| <b>A15</b>                                           |                            |              |      |              |                            |                          |                  |                  |                               |
| MOL : 3 1/2 in. (89 mm) LCL : 2 3/8 in. (60 mm)      |                            |              |      |              |                            |                          |                  |                  |                               |
| 50125                                                | 15A15/CL/5M/130V/STD       | 15           | E26  | 130          | 85                         | 5 000                    | C-9              | Clear            | 6/60                          |
| 50166                                                | 15A15/F/5M/130V/STD        | 15           | E26  | 130          | 80                         | 5 000                    | C-9              | Frost            | 6/60                          |
| 50145                                                | 25A15/CL/5M/130V/STD       | 25           | E26  | 130          | 135                        | 5 000                    | C-9              | Clear            | 6/60                          |
| 50126                                                | 25A15/F/5M/130V/STD        | 25           | E26  | 130          | 135                        | 5 000                    | C-9              | Frost            | 6/60                          |
| <b>A19</b>                                           |                            |              |      |              |                            |                          |                  |                  |                               |
| MOL : 4 1/4 in. (108 mm) LCL : 3 1/8 in. (79 mm)     |                            |              |      |              |                            |                          |                  |                  |                               |
| 50941                                                | 15A19/CL/6M/130V/STD       | 15           | E26  | 130          | 80                         | 6 000                    | C-9              | Clear            | 6/120                         |
| 50931                                                | 25A19/CL/1M/120V/STD/4P    | 25           | E26  | 120          | 150                        | 1 000                    | C-9              | Clear            | 6/120                         |
| <b>B8</b>                                            |                            |              |      |              |                            |                          |                  |                  |                               |
| MOL : 3 5/32 in. (80 mm) LCL : 1 7/8 in. (48 mm)     |                            |              |      |              |                            |                          |                  |                  |                               |
| 50635                                                | 15B8/F/2.5M/E12/130V/STD   | 15           | E12  | 130          | 70                         | 2 500                    | C-7A             | Frost            | 6/120                         |
| 50639                                                | 25B8/F/2.5M/E12/130V/STD   | 25           | E12  | 130          | 115                        | 2 500                    | C-7A             | Frost            | 6/120                         |
| <b>B10</b>                                           |                            |              |      |              |                            |                          |                  |                  |                               |
| MOL : 3 29/32 in. (99 mm) LCL : 1 25/32 in. (45 mm)  |                            |              |      |              |                            |                          |                  |                  |                               |
| 50611                                                | 15B10/CL/3M/E12/130V/STD   | 15           | E12  | 130          | 75                         | 3 000                    | C-7A             | Clear            | 6/120                         |
| 50543                                                | 25B10/CL/3M/E12/130V/STD   | 25           | E12  | 130          | 165                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| 50612                                                | 25B10/F/3M/E12/130V/STD    | 25           | E12  | 130          | 165                        | 3 000                    | CC-2V            | Frost            | 6/120                         |
| MOL : 3 1/2 in. (89 mm) LCL : 2 1/8 in. (54 mm)      |                            |              |      |              |                            |                          |                  |                  |                               |
| 50621                                                | 25B10/CL/3M/130V/STD       | 25           | E26  | 130          | 165                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| MOL : 3 31/32 in. (101 mm) LCL : 1 25/32 in. (45 mm) |                            |              |      |              |                            |                          |                  |                  |                               |
| 50548                                                | 25B10/CL/3M/E14/130V/STD   | 25           | E14  | 130          | 165                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| <b>B10 Suitable for base up</b>                      |                            |              |      |              |                            |                          |                  |                  |                               |
| MOL : 3 1/2 in. (89 mm) LCL : 2 1/8 in. (54 mm)      |                            |              |      |              |                            |                          |                  |                  |                               |
| 50624                                                | 25B10/F/3M/130V/STD        | 25           | E26  | 130          | 165                        | 3 000                    | CC-2V            | Frost            | 6/120                         |
| 50622                                                | 40B10/CL/3M/130V/STD       | 40           | E26  | 130          | 280                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| 50625                                                | 40B10/F/3M/130V/STD        | 40           | E26  | 130          | 280                        | 3 000                    | CC-2V            | Frost            | 6/120                         |
| MOL : 3 29/32 in. (99 mm) LCL : 1 25/32 in. (45 mm)  |                            |              |      |              |                            |                          |                  |                  |                               |
| 50544                                                | 40B10/CL/3M/E12/130V/STD   | 40           | E12  | 130          | 280                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| 50613                                                | 40B10/F/3M/E12/130V/STD    | 40           | E12  | 130          | 280                        | 3 000                    | CC-2V            | Frost            | 6/120                         |
| 50545                                                | 60B10/CL/3M/E12/130V/STD   | 60           | E12  | 130          | 430                        | 3 000                    | C-7A/3           | Clear            | 6/120                         |
| 50614                                                | 60B10/F/3M/E12/130V/STD    | 60           | E12  | 130          | 430                        | 3 000                    | C-7A/3           | Frost            | 6/120                         |
| MOL : 3 31/32 in. (101 mm) LCL : 1 25/32 in. (45 mm) |                            |              |      |              |                            |                          |                  |                  |                               |
| 50549                                                | 40B10/CL/3M/E14/130V/STD   | 40           | E14  | 130          | 280                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| 50552                                                | 40B10/F/3M/E14/130V/STD    | 40           | E14  | 130          | 280                        | 3 000                    | CC-2V            | Frost            | 6/120                         |
| 50550                                                | 60B10/CL/3M/E14/130V/STD   | 60           | E14  | 130          | 430                        | 3 000                    | C-7A/3           | Clear            | 6/120                         |
| 50553                                                | 60B10/F/3M/E14/130V/STD    | 60           | E14  | 130          | 430                        | 3 000                    | C-7A/3           | Frost            | 6/120                         |
| <b>BR30</b>                                          |                            |              |      |              |                            |                          |                  |                  |                               |
| MOL : 5 1/8 in. (130 mm) LCL : 3 11/32 in. (85 mm)   |                            |              |      |              |                            |                          |                  |                  |                               |
| 50219                                                | 50BR30/FL/5M/130V/STD      | 50           | E26  | 130          | 240                        | 5 000                    | C-9              | Frost            | 6/60                          |
| 50077                                                | 65BR30/FL/5M/ES/130V/STD   | 65           | E26  | 130          | 470                        | 5 000                    | CC-6             | Frost            | 6/60                          |
| <b>BR40</b>                                          |                            |              |      |              |                            |                          |                  |                  |                               |
| MOL : 6 9/16 in. (167 mm) LCL : 4 1/4 in. (108 mm)   |                            |              |      |              |                            |                          |                  |                  |                               |
| 50080 <sup>1</sup>                                   | 65BR40/FL/5M/ES/130V/STD   | 65           | E26  | 130          | 470                        | 5 000                    | CC-6             | Clear            | 1/12                          |
| <b>C7</b>                                            |                            |              |      |              |                            |                          |                  |                  |                               |
| MOL : 2 1/8 in. (54 mm) LCL : 1 1/2 in. (38 mm)      |                            |              |      |              |                            |                          |                  |                  |                               |
| 50308                                                | 7C7/CL/3M/E12/125V/STD 10P | 7            | E12  | 125          | 26                         | 3 000                    | C-7A             | Clear            | 10/500                        |

<sup>1</sup> This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

## Incandescent Lamps

| Order<br>code                                       | Description                     | Watts<br>(W) | Base | Volts<br>(V) | Lumens<br>at 120 V<br>(lm) | Average<br>life<br>(hrs) | Filament<br>type | Finish | Case<br>qty<br>(inner/master) |
|-----------------------------------------------------|---------------------------------|--------------|------|--------------|----------------------------|--------------------------|------------------|--------|-------------------------------|
| <b>CA4.5</b>                                        |                                 |              |      |              |                            |                          |                  |        |                               |
| MOL : 2 3/4 in. (70 mm) LCL : 1 5/8 in. (41 mm)     |                                 |              |      |              |                            |                          |                  |        |                               |
| 52153                                               | 10CA4.5/CL/2M/E12/130V/STD      | 10           | E12  | 130          | 40                         | 2 000                    | C-7A             | Clear  | 6/120                         |
| <b>CA8</b>                                          |                                 |              |      |              |                            |                          |                  |        |                               |
| MOL : 3 19/32 in. (91 mm) LCL : 1 25/32 in. (45 mm) |                                 |              |      |              |                            |                          |                  |        |                               |
| 52157                                               | 10CA8/F/2.5M/E12/130V/STD       | 10           | E12  | 130          | 50                         | 2 500                    | C-7A             | Frost  | 25/500                        |
| 50641                                               | 15CA8/CL/2.5M/E12/130V/STD      | 15           | E12  | 130          | 70                         | 2 500                    | C-7A             | Clear  | 6/120                         |
| 10269                                               | 15CA8/F/2.5M/E12/130V/STD       | 15           | E12  | 130          | 70                         | 2 500                    | C-7A             | Frost  | 25/500                        |
| 50643                                               | 25CA8/F/2.5M/E12/130V/STD       | 25           | E12  | 130          | 115                        | 2 500                    | C-7A             | Frost  | 6/120                         |
| 50642                                               | 40CA8/CL/2.5M/E12/130V/STD      | 40           | E12  | 130          | 215                        | 2 500                    | C-7A             | Clear  | 25/500                        |
| 50644                                               | 40CA8/F/2.5M/E12/130V/STD       | 40           | E12  | 130          | 215                        | 2 500                    | C-7A             | Frost  | 25/500                        |
| <b>CA10</b>                                         |                                 |              |      |              |                            |                          |                  |        |                               |
| MOL : 3 29/32 in. (99 mm) LCL : 2 1/8 in. (54 mm)   |                                 |              |      |              |                            |                          |                  |        |                               |
| 51051                                               | 25CA10/CL/3M/130V/STD           | 25           | E26  | 130          | 120                        | 3 000                    | C-7A             | Clear  | 6/120                         |
| 50629                                               | 25CA10/F/3M/130V/STD            | 25           | E26  | 130          | 115                        | 3 000                    | C-7A             | Frost  | 6/120                         |
| MOL : 4 3/32 in. (104 mm) LCL : 1 7/8 in. (48 mm)   |                                 |              |      |              |                            |                          |                  |        |                               |
| 50615                                               | 25CA10/CL/3M/E12/130V/STD       | 25           | E12  | 130          | 135                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50618                                               | 25CA10/F/3M/E12/130V/STD        | 25           | E12  | 130          | 115                        | 3 000                    | CC-2V            | Frost  | 6/120                         |
| 50616                                               | 40CA10/CL/3M/E12/130V/STD       | 40           | E12  | 130          | 235                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50619                                               | 40CA10/F/3M/E12/130V/STD        | 40           | E12  | 130          | 205                        | 3 000                    | CC-2V            | Frost  | 6/120                         |
| 50617                                               | 60CA10/CL/3M/E12/130V/STD       | 60           | E12  | 130          | 455                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50620                                               | 60CA10/F/3M/E12/130V/STD        | 60           | E12  | 130          | 450                        | 3 000                    | CC-2V            | Frost  | 6/120                         |
| <b>F15</b>                                          |                                 |              |      |              |                            |                          |                  |        |                               |
| MOL : 4 1/2 in. (115 mm) LCL : 2 9/16 in. (65 mm)   |                                 |              |      |              |                            |                          |                  |        |                               |
| 69853                                               | 40F15/CL/1.5M/130V/STD S2       | 40           | E26  | 130          | 305                        | 1 500                    | CC-6             | Clear  | 6/24                          |
| <b>G9.5</b>                                         |                                 |              |      |              |                            |                          |                  |        |                               |
| MOL : 2 1/16 in. (52 mm) LCL : 1 1/2 in. (38 mm)    |                                 |              |      |              |                            |                          |                  |        |                               |
| 52165                                               | 7.5G9.5/CL/1M/E12/130V/STD      | 7            | E12  | 130          | 40                         | 1 000                    | C-7A             | Clear  | 25/500                        |
| <b>G11</b>                                          |                                 |              |      |              |                            |                          |                  |        |                               |
| MOL : 2 5/16 in. (59 mm) LCL : 1 5/8 in. (41 mm)    |                                 |              |      |              |                            |                          |                  |        |                               |
| 69785                                               | 7.5G11/CL/1M/E12/130V/STD S2    | 7.5          | E12  | 130          | 40                         | 1 000                    | C-7A/3           | Clear  | 6/120                         |
| 69787                                               | 7.5G11/CL/1M/130V/STD S2        | 7.5          | E26  | 130          | 40                         | 1 000                    | C-7A/3           | Clear  | 6/120                         |
| <b>G13</b>                                          |                                 |              |      |              |                            |                          |                  |        |                               |
| MOL : 2 3/8 in. (60.5 mm) LCL : 1 11/16 in. (43 mm) |                                 |              |      |              |                            |                          |                  |        |                               |
| 50681                                               | 10G13/CL/3M/E12/130V/STD        | 10           | E12  | 130          | 50                         | 3 000                    | C-7A             | Clear  | 25/500                        |
| 50682                                               | 25G13/CL/3M/E12/130V/STD        | 25           | E12  | 130          | 135                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| <b>G16.5</b>                                        |                                 |              |      |              |                            |                          |                  |        |                               |
| MOL : 3 in. (76 mm) LCL : 1 7/8 in. (48 mm)         |                                 |              |      |              |                            |                          |                  |        |                               |
| 10334                                               | 5G16.5/CL/3M/E12/130V/STD       | 5            | E12  | 130          | 20                         | 3 000                    | C-7A             | Clear  | 6/120                         |
| 10268                                               | 10G16.5/CL/3M/E12/130V/STD      | 10           | E12  | 130          | 50                         | 3 000                    | C-7A             | Clear  | 6/120                         |
| 50660                                               | 15G16.5/CL/3M/E12/130V/STD      | 15           | E12  | 130          | 70                         | 3 000                    | C-7A             | Clear  | 6/120                         |
| 50662                                               | 15G16.5/WH/3M/E12/130V/STD      | 15           | E12  | 130          | 60                         | 3 000                    | C-7A             | White  | 6/120                         |
| 50652                                               | 25G16.5/WH/3M/E12/130V/STD      | 25           | E12  | 130          | 120                        | 3 000                    | CC-2V            | White  | 6/120                         |
| 52453                                               | 25G16.5/CL/3M/E12/130V/ELUME 2P | 25           | E12  | 130          | 160                        | 3 000                    | C-7A             | Clear  | 24/120                        |
| 50777                                               | 25G16.5/CL/3M/E14/130V/STD      | 25           | E14  | 130          | 160                        | 3 000                    | CC-6             | Clear  | 6/120                         |
| 50649                                               | 25G16.5/CL/3M/130V/STD          | 25           | E26  | 130          | 135                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50653                                               | 25G16.5/WH/3M/130V/STD          | 25           | E26  | 130          | 120                        | 3 000                    | CC-2V            | White  | 6/120                         |
| 50654                                               | 40G16.5/WH/3M/E12/130V/STD      | 40           | E12  | 130          | 230                        | 3 000                    | CC-2V            | White  | 6/120                         |
| 52454                                               | 40G16.5/CL/3M/E12/130V/ELUME 2P | 40           | E12  | 130          | 160                        | 3 000                    | C-7A             | Clear  | 24/120                        |
| 50651                                               | 40G16.5/CL/3M/130V/STD          | 40           | E26  | 130          | 250                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50655                                               | 40G16.5/WH/3M/130V/STD          | 40           | E26  | 130          | 230                        | 3 000                    | CC-2V            | White  | 6/120                         |
| 50656                                               | 60G16.5/CL/3M/E12/130V/STD      | 60           | E12  | 130          | 440                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50658                                               | 60G16.5/WH/3M/E12/130V/STD      | 60           | E12  | 130          | 400                        | 3 000                    | CC-2V            | White  | 6/120                         |

| Order<br>code                                        | Description                | Watts<br><br>(W) | Base | Volts<br><br>(V) | Lumens<br>at 120 V<br>(lm) | Average<br>life<br>(hrs) | Filament<br>type | Finish     | Case<br>qty<br>(inner/master) |
|------------------------------------------------------|----------------------------|------------------|------|------------------|----------------------------|--------------------------|------------------|------------|-------------------------------|
| <b>G16.5 (cont.)</b>                                 |                            |                  |      |                  |                            |                          |                  |            |                               |
| MOL : 2 7/8 in. (73 mm) LCL : 2 1/16 in. (52 mm)     |                            |                  |      |                  |                            |                          |                  |            |                               |
| 50779                                                | 25G16.5/WH/3M/E14/130V/STD | 25               | E14  | 130              | 150                        | 3 000                    | CC-6             | White      | 25/500                        |
| 50782                                                | 60G16.5/WH/3M/E14/130V/STD | 60               | E14  | 130              | 580                        | 3 000                    | CC-6             | White      | 25/500                        |
| <b>G25</b>                                           |                            |                  |      |                  |                            |                          |                  |            |                               |
| MOL : 2 1/2 in. (114 mm) LCL : 3 1/32 in. (77 mm)    |                            |                  |      |                  |                            |                          |                  |            |                               |
| 50199                                                | 25G25/CL/3M/130V/STD       | 25               | E26  | 130              | 135                        | 3 000                    | C-9              | Clear      | 6/60                          |
| 50196                                                | 25G25/WH/3M/130V/STD       | 25               | E26  | 130              | 115                        | 3 000                    | C-9              | White      | 6/60                          |
| 50222                                                | 40G25/CL/3M/130V/STD       | 40               | E26  | 130              | 255                        | 3 000                    | C-9              | Clear      | 6/60                          |
| 50155                                                | 40G25/WH/3M/130V/STD       | 40               | E26  | 130              | 230                        | 3 000                    | C-9              | White      | 6/60                          |
| <b>G30</b>                                           |                            |                  |      |                  |                            |                          |                  |            |                               |
| MOL : 5 13/32 in. (137 mm) LCL : 3 9/32 in. (83 mm)  |                            |                  |      |                  |                            |                          |                  |            |                               |
| 50203                                                | 25G30/CL/3M/130V/STD       | 25               | E26  | 130              | 115                        | 3 000                    | C-9              | Clear      | 6/60                          |
| 50204                                                | 40G30/CL/3M/130V/STD       | 40               | E26  | 130              | 230                        | 3 000                    | C-9              | Clear      | 6/60                          |
| 50202                                                | 40G30/WH/3M/130V/STD       | 40               | E26  | 130              | 215                        | 3 000                    | C-9              | White      | 6/60                          |
| <b>G40</b>                                           |                            |                  |      |                  |                            |                          |                  |            |                               |
| MOL : 6 15/16 in. (176 mm) LCL : 3 29/32 in. (99 mm) |                            |                  |      |                  |                            |                          |                  |            |                               |
| 50205                                                | 25G40/CL/3M/130V/STD       | 25               | E26  | 130              | 100                        | 3 000                    | C-9              | Clear      | 6/12                          |
| 50150                                                | 40G40/WH/3M/130V/STD       | 40               | E26  | 130              | 215                        | 3 000                    | C-9              | White      | 6/12                          |
| 50111                                                | 60G40/CL/3M/130V/STD       | 60               | E26  | 130              | 465                        | 3 000                    | C-9              | Clear      | 6/12                          |
| 50210                                                | 100G40/WH/3M/130V/STD      | 100              | E26  | 130              | 820                        | 3 000                    | C-9              | White      | 6/12                          |
| 50112                                                | 150G40/WH/3M/130V/STD      | 150              | E26  | 130              | 1 175                      | 3 000                    | C-9              | White      | 6/12                          |
| <b>PS25</b>                                          |                            |                  |      |                  |                            |                          |                  |            |                               |
| MOL : 6 15/16 in. (176 mm) LCL : 5 1/32 in. (128 mm) |                            |                  |      |                  |                            |                          |                  |            |                               |
| 50071                                                | 300PS25/CL/5M/130V/STD     | 300              | E26  | 130              | 2 725                      | 5 000                    | C-9              | Clear      | 6/24                          |
| 50088                                                | 300PS25/F/5M/130V/STD      | 300              | E26  | 130              | 2 725                      | 5 000                    | C-9              | Frost      | 6/24                          |
| <b>PS35</b>                                          |                            |                  |      |                  |                            |                          |                  |            |                               |
| MOL : 9 13/32 in. (239 mm) LCL : 6 1/2 in. (165 mm)  |                            |                  |      |                  |                            |                          |                  |            |                               |
| 50225                                                | 300PS35/CL/5M/E39/130V/STD | 300              | E39  | 130              | 2 725                      | 5 000                    | C-9              | Clear      | 6/24                          |
| <b>R14</b>                                           |                            |                  |      |                  |                            |                          |                  |            |                               |
| MOL : 2 1/8 in. (54 mm) LCL : 1 21/32 in. (42 mm)    |                            |                  |      |                  |                            |                          |                  |            |                               |
| 50665                                                | 25R14/FL/1.5M/120V/STD     | 25               | E26  | 120              | 150                        | 1 500                    | CC-2V            | Clear      | 6/120                         |
| 50663                                                | 40R14/F/FL/1.5M/120V/STD   | 40               | E26  | 120              | 280                        | 1 500                    | CC-2V            | Frost      | 6/120                         |
| <b>R16</b>                                           |                            |                  |      |                  |                            |                          |                  |            |                               |
| MOL : 3 1/2 in. (89 mm)                              |                            |                  |      |                  |                            |                          |                  |            |                               |
| 52168                                                | 25R16/SF/1.5M/E12/130V/STD | 25               | E12  | 130              | 120                        | 3 000                    | CC-2V            | Frost      | 25/500                        |
| 52459                                                | 40R16/SW/1M/120V/ELUME 2P  | 40               | E26  | 120              | 445                        | 1 000                    | CC-6             | Soft white | 12/60                         |
| 52460                                                | 60R16/SW/1M/130V/ELUME 2P  | 60               | E26  | 130              | 730                        | 1 000                    | CC-6             | Soft white | 12/60                         |
| <b>R19</b>                                           |                            |                  |      |                  |                            |                          |                  |            |                               |
| MOL : 3 31/32 in. (101 mm) LCL : 3 1/32 in. (77 mm)  |                            |                  |      |                  |                            |                          |                  |            |                               |
| 50136                                                | 40R19/SW/1.5M/120V/STD     | 40               | E26  | 120              | 320                        | 1 500                    | CC-6             | Soft white | 6/60                          |
| <b>R20</b>                                           |                            |                  |      |                  |                            |                          |                  |            |                               |
| MOL : 3 29/32 in. (99 mm) LCL : 2 15/16 in. (75 mm)  |                            |                  |      |                  |                            |                          |                  |            |                               |
| 50211                                                | 30R20/SP/5M/130V/STD       | 30               | E26  | 130              | 145                        | 5 000                    | C-9              | Clear      | 6/60                          |
| 61707                                                | 45R20/FL/5M/130V/ELUME 2P  | 45               | E26  | 130              | 242                        | 5 000                    | CC-7             | Frost      | 6/60                          |
| 61705                                                | 45R20/SP/5M/130V/STD       | 45               | E26  | 130              | 242                        | 5 000                    | CC-6             | Frost      | 6/60                          |

# Incandescent Lamps

| Order code                                           | Description                  | Watts<br>(W) | Base  | Volts<br>(V) | Lumens<br>at 120 V<br>(lm) | Average<br>life<br>(hrs) | Filament<br>type | Finish/<br>Color | Case<br>qty<br>(inner/master) |
|------------------------------------------------------|------------------------------|--------------|-------|--------------|----------------------------|--------------------------|------------------|------------------|-------------------------------|
| <b>S11</b>                                           |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 2 5/16 in. (59 mm) LCL : 1 1/2 in. (38 mm)     |                              |              |       |              |                            |                          |                  |                  |                               |
| 50789                                                | 5S11/CL/1M/E17/130V/STD      | 5            | E17   | 130          | 25                         | 1 000                    | C-7A             | Clear            | 25/500                        |
| 50143                                                | 10S11/CL/1M/E17/130V/STD     | 10           | E17   | 130          | 60                         | 1 000                    | C-7A             | Clear            | 6/120                         |
| 50786                                                | 25S11/CL/1M/E17/130V/STD     | 25           | E17   | 130          | 130                        | 1 000                    | C-7A             | Clear            | 25/500                        |
| 50123                                                | 40S11/CL/1M/E17/130V/STD     | 40           | E17   | 130          | 275                        | 1 000                    | C-7A             | Clear            | 6/120                         |
| <b>S14</b>                                           |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 2 5/16 in. (59 mm) LCL : 1 1/2 in. (38 mm)     |                              |              |       |              |                            |                          |                  |                  |                               |
| 59542                                                | 11S14/CL/8M/130V/STD         | 11           | E26   | 130          | 40                         | 8 000                    | C-9              | Clear            | 6/24                          |
| 50147                                                | 11S14/CL/3M/130V/STD         | 11           | E26   | 130          | 72                         | 3 000                    | C-9              | Clear            | 25/500                        |
| <b>T6</b>                                            |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 3 1/16 in. (78 mm) LCL : 1 9/16 in. (40 mm)    |                              |              |       |              |                            |                          |                  |                  |                               |
| 50667                                                | 15T6/CL/7.5M/E12/130V/STD    | 15           | E12   | 130          | 75                         | 7 500                    | C-5A             | Clear            | 12/120                        |
| 50668                                                | 15T6/CL/7.5M/E12/145V/STD    | 15           | E12   | 145          | 90                         | 7 500                    | C-5A             | Clear            | 12/120                        |
| 50675                                                | 15T6/CL/5M/E17/130V/STD      | 15           | E17   | 130          | 70                         | 5 000                    | C-5A             | Clear            | 12/120                        |
| 50676                                                | 15T6/CL/7.5M/E17/145V/STD    | 15           | E17   | 145          | 90                         | 7 500                    | C-5A             | Clear            | 12/120                        |
| <b>T6.5</b>                                          |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 5 13/32 in. (137 mm) LCL : 3 5/32 in. (80 mm)  |                              |              |       |              |                            |                          |                  |                  |                               |
| 51052                                                | 20T6.5/CL/5M/BA15d/130V/STD  | 20           | BA15d | 130          | 115                        | 5 000                    | C-8              | Clear            | 25/500                        |
| 50679                                                | 20T6.5/F/5M/BA15d/130V/STD   | 20           | BA15d | 130          | 115                        | 5 000                    | C-8              | Frost            | 12/120                        |
| 51056                                                | 25T6.5/CL/5M/BA15d/125V/STD  | 25           | BA15d | 125          | 180                        | 5 000                    | C-8              | Clear            | 25/500                        |
| 50729                                                | 25T6.5/F/7.5M/BA15d/145V/STD | 25           | BA15d | 145          | 145                        | 7 500                    | C-8              | Frost            | 25/500                        |
| 50672                                                | 25T6.5/CL/7.5M/E12/145V/STD  | 25           | E12   | 145          | 180                        | 7 500                    | C-8              | Clear            | 12/120                        |
| 50669                                                | 25T6.5/CL/5M/E17/130V/STD    | 25           | E17   | 130          | 135                        | 5 000                    | C-8              | Clear            | 12/120                        |
| 50670                                                | 25T6.5/CL/7.5M/E17/145V/STD  | 25           | E17   | 145          | 180                        | 7 500                    | C-8              | Clear            | 12/120                        |
| 50673                                                | 25T6.5/F/7.5M/E17/145V/STD   | 25           | E17   | 145          | 180                        | 7 500                    | C-8              | Frost            | 25/500                        |
| <b>T7</b>                                            |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 2 5/16 in. (59 mm) LCL : 1 5/16 in. (33 mm)    |                              |              |       |              |                            |                          |                  |                  |                               |
| 52195                                                | 15T7/CL/1.5M/BA15d/120V/STD  | 15           | BA15d | 120          | 100                        | 1 500                    | C-7A             | Clear            | 25/1 000                      |
| 52196                                                | 15T7/F/1.5M/BA15d/130V/STD   | 15           | BA15d | 130          | 75                         | 1 500                    | C-7A             | Frost            | 25/1 000                      |
| 52201                                                | 25T7/CL/1.5M/E12/130V/STD    | 25           | E12   | 130          | 115                        | 1 500                    | C-7A             | Clear            | 25/1 000                      |
| <b>T8</b>                                            |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 2 9/16 in. (65 mm) LCL : 1 5/8 in. (41 mm)     |                              |              |       |              |                            |                          |                  |                  |                               |
| 52198                                                | 25T8/CL/1.5M/BA15d/120V/STD  | 25           | BA15d | 120          | 220                        | 1 500                    | C-7A             | Clear            | 25/1 000                      |
| 69795                                                | 25T8/CL/1.5M/E12/120V/STD    | 25           | E12   | 120          | 220                        | 1 500                    | C-5A             | Clear            | 12/120                        |
| 52197                                                | 25T8/CL/1.5M/E17/120V/STD    | 25           | E17   | 120          | 220                        | 1 500                    | C-7A             | Clear            | 25/1 000                      |
| <b>T10</b>                                           |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 5 in. (127 mm) LCL : 2 3/4 in. (70 mm)         |                              |              |       |              |                            |                          |                  |                  |                               |
| 50925                                                | 25T10/CL/3M/130V/STD         | 25           | E26   | 130          | 135                        | 3 000                    | C-5V             | Clear            | 6/120                         |
| 50928                                                | 25T10/F/3M/130V/STD          | 25           | E26   | 130          | 135                        | 3 000                    | C-5V             | Frost            | 6/120                         |
| 50926                                                | 40T10/CL/3M/130V/STD         | 40           | E26   | 130          | 195                        | 3 000                    | C-5V             | Clear            | 6/120                         |
| 50929                                                | 40T10/F/3M/130V/STD          | 40           | E26   | 130          | 195                        | 3 000                    | C-5V             | Frost            | 6/120                         |
| <b>T10 HO</b>                                        |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 5 13/32 in. (137 mm) LCL : 3 11/32 in. (85 mm) |                              |              |       |              |                            |                          |                  |                  |                               |
| 50129                                                | 40T10/CL/3M/HO/130V/STD      | 40           | E26   | 130          | 300                        | 3 000                    | C-8              | Clear            | 6/120                         |