

Specialty



MOL : 4 1/2 in. (114 mm)
Ø 25/32 in. (20 mm)
LCL : 2 5/16 in. (69 mm)

T6



MOL : 5 3/16 in. (132 mm)
Ø 29/32 in. (23 mm)
LCL : 2 13/16 in. (61 mm)

T7



MOL : 11 1/2 in. (292 mm)
Ø 4 19/25 in. (121 mm)
LCL : 7 in. (178 mm)

ED37

Order code	Description	Shape	Base	ANSI code	Color temp. (K)	Lumen output (lm)	Mean lumens (lm)	Average life (hrs)	CRI	Operating position	Finish	Luminaire	Case qty (master)
70 watts													
57975	MH-DE 70W/UVS/4K STD	T6	R7s	M85/E	4 200	5 500	3 600	10 000	65	HOR±45°	Clear	E	25
68869	MH-DE 70W/UVS/3K STD	T6	R7s	M85/E	3 000	5 500	4 250	6 000	65	HOR±45°	Clear	E	144
150 watts													
59141	MH-DE 150W/UVS/3K STD	T7	R7s	M81/E	3 000	11 250	8 400	10 000	65	HOR±45°	Clear	E	25
360 watts													
68526	MPI360W/BU/EM STD	ED37	EX39	M165/M59/O	4 200	36 000	28 800	20 000	65	BU±15°	Clear	O	6

Ceramic Metal Halide



35W: MOL : 3 15/16 in. (100 mm)
70W: MOL : 3 3/4 in. (96 mm)
Ø 3/4 in. (19 mm)
LCL : 2 7/32 in. (66 mm)

T6



MOL : 4 13/16 in. (122 mm)
Ø 3 3/4 in. (95 mm)

PAR30LN



MOL : 3 11/32 in. (85 mm)
LCL : 2 1/16 in. (52 mm)

T4.5

Order code	Description	Shape	Base	Color temp. (K)	Average life (h)	Initial lumens (lm)	Mean lumens (lm)	CRI	Operating position	Finish	Luminaire	Case qty (master)
35 watts												
59993	CMH35PAR30LN/830/FL/STD	PAR30LN	E26	3 000	8 000	2 200	1 804	80	U	Clear	O	6
68875	CMT35/U/830/G12/STD	T6	G12	3 000	10 000	3 400	2 890	80	U	Clear	E	12
69171	CMT35/U/830/G8.5/STD	T4.5	G8.5	3 000	10 000	3 400	2 890	85	U	Clear	E	12
70 watts												
68876	CMT70/U/830/G12/STD	T6	G12	3 000	15 000	7 000	5 950	85	U	Clear	U	12

O = Open rated for indoor fixtures E = Enclosed rated for indoor or outdoor fixtures
Note: Lamp description containing UVS have the UV Stop feature.