

High Pressure Sodium



MOL.: 11 1/2 in. (292 mm)
Ø 4 5/8 in. (117.5 mm)
LCL.: 7 in. (178 mm)

ED23.5



MOL.: 11 1/2 in. (292 mm)
Ø 4 5/8 in. (117.5 mm)
LCL.: 7 in. (178 mm)

ED17



MOL.: 11 1/2 in. (292 mm)
Ø 4 5/8 in. (117.5 mm)
LCL.: 7 in. (178 mm)

ET18



MOL.: 11 1/2 in. (292 mm)
Ø 4 5/8 in. (117.5 mm)
LCL.: 7 in. (178 mm)

E25

Order code	Description	Shape	Base	ANSI code	Color temp. (K)	Lumen output (lm)	Mean lumens (lm)	Average life (hrs)	CRI	Operating position	Finish	Luminaire	Case qty (master)
35 watts													
62654	LU35/MED LT EYE	ED17	E26	S76/E	2 000	2 200	2 050	16 000	20	U	Clear	E	12
50 watts													
70160	LU50/MED STD	ED17	E26	S68/E	1 900	4 000	3 600	24 000	22	U	Clear	E	12
70159	LU50/ECO STD	ED23.5	E39	S68/E	1 900	4 000	3 600	24 000	22	U	Clear	E	12
70 watts													
70162	LU70/MED STD	ED17	E26	S62/E	1 900	6 300	5 350	24 000	22	U	Clear	E	12
100 watts													
70152	LU100/MED STD	ED17	E26	S54/E	1 900	9 500	8 000	24 000	22	U	Clear	E	12
70151	LU100/ECO STD	ED23.5	E39	S54/E	1 900	9 500	8 550	24 000	22	U	Clear	E	12
150 watts													
70155	LU150/MED STD	ED17	E26	S55/E	2 000	15 000	13 800	24 000	20	U	Clear	E	12
250 watts													
62653	LU250/EN LT EYE	ET18	E39	S50/E	2 000	28 000	26 100	24 000	20	U	Clear	E	12
400 watts													
62655	LU400/EN LT EYE	ET18	E39	S51/E	2 000	48 000	45 000	28 000	20	U	Clear	E	12
1000 watts													
62649	LU1000B/EN LT EYE	E25	E39	S52/E	2 000	140 000	126 000	24 000	30	U	Clear	E	12

E = Enclosed rated for indoor or outdoor fixtures