


Choose the right LED Downlight

All of our LED downlights are available in quick ship and certified Energy Star.



		LPDL - Low profile downlight				Swivel	Gimbal		Stellar	Retro Gen 2	COMETO Fire-rated	COMETO Commercial	CDU Gen 2
		Regressed	Stanpro	Choice	Eco Choice	Choice	Gimbal 7 W	Gimbal 12 W				Choice	
													
Main selling features		Glare-free design for enhanced illuminance	Variety of sizes and colors	Quality-Price	Economical solution	Directional downlight which can highlight specific zones with 360° rotation and up to 90° tilt	Small aperture and highly versatile design with directional light output	Outstanding performance, small aperture and regressed design with directional light output	Small aperture and sleek design	Retrofit solution with E26 screw-in adaptor for existing recessed cans, easy installation	Slim backlit downlight, designed and tested to meet fire-resistance standards.	Slim backlit commercial downlight with 5 CCT and 3 power selectables	All-in-one commercial downlight with integrated 3 CCT and 3 power selectable
Size(s) (in)		4, 6	3, 4, 6	4, 6	4	4	3, 4	3.5	2	4, 5-6	4, 6	4, 6, 8	4, 6, 8
Shape													
Watts (W)		9, 12	7, 7.5, 12	9, 12	9	8, 9	7	12	12	10, 15	11, 12	8/10/12 12/15/18 18/20/25	7/9/12 12/16/20 15/20/25
Lumen output (lm)		750, 1 200	580, 620, 1 000	800, 1 050	750	Single CCT : 750 CCT Selectable : Up to 650	Warm Dim : 470 Single CCT : Up to 620	Warm Dim : 660 Single CCT : Up to 950 CCT Selectable : 850	Warm Dim : 850 CCT Selectable : 1 000	820, 1 250	750, 1 000	750/900/1 000 1 200/1 500/1 800 1 700/2 200/2 800	595/765/1 000 1 080/1 440/2 000 1 800/2 200/2 900
Volts (VAC)		120	120	120	120	120	120	120 120-277 ²	120	120	120	120-347	120-347
Color Temp. (K)	Single					3 000	3 000, 4 000	3 000, 4 000					
	Warm Dim						3 000-2 200	3 000-2 200	3 000-2 200				
	Selectable	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	3 CCT : 2 700/3 000/4 000		5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	3 CCT : 3 000/3 500/4 000
Color finish													
CRI		90+	90+	90+	90+	90+	80+, 90+	90+	90+	90+	80+	80+	80+
Beam angle		 Directional Diffused											
Location		 Dry  Damp  Wet						 ¹					
Dimmable		ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	0-10 V ²	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	0-10 V	0-10 V
Cable rated		FT4	FT6	FT4	FT4	FT4	FT4	FT6	FT6		FT6	FT6	
Warranty (year)		5	7	5	3	5	5	5	5	5	5	5	5
IC rated		✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓
Airtight		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Other details							Interchangeable trims, increase flexibility and reduce inventory level	Available in individual bulk pack of 10 drivers and 10 LED modules for 2-phases job site deliveries ³	Interchangeable Black trim ⁴		2-hour fire-resistant steel housing		

¹ Only available with 5CCT selectable LED module

² Only available with bulk pack option

³ Only available in 3.5" 30K white

⁴ Sold separately