

EBST-MVP

PURE-SINE WAVE IPS MINI-INVERTER



Normally OFF: By combining a battery unit and off-line inverter with superior 120 V or 347 V lighting performance for all types of lighting fixtures, the EBST-MVP provides exceptional power failure lighting. The typically configured battery unit is paired with an off-line, internally mounted, pure-sine wave inverter. When AC power is present there is no output and the connected fixtures are off, when the AC power fails, the unit outputs 120 V AC or 347 V AC to the connected lighting fixtures at 100% brightness.

Normally ON: This feature is easily activated by connecting a normally-ON lighting circuit to the unit. When AC power is present there is output and the connected lighting fixtures are on. When the AC power fails, the output is then transferring to the power failure mode of the inverter and the connected lighting fixtures stay on.

FEATURES & SPECIFICATIONS

CIRCUITRY

- 120 V AC input / 120 V AC output or 347 V AC input / 347 V AC output
- Transfer time of 2 seconds
- Momentary push button test switch
- Diagnostic/pilot LEDs for AC ON and CHARGE
- Fully automatic, current limited charger
- Line latched, low voltage protection
- Brownout and short circuit protection
- Terminal block connectors for output load
- Dimming override control is standard
- Auto transfer switch for normally-on lighting circuit
- Maintenance free, sealed lead acid battery[s]

Overload protectors:



- 1000 W: Fuse allowing max load of 175A and board protector with protection up to 1100 W
- 1440 W: Fuse allowing max load of 175A and board protector with protection up to 1500 W
- Optional automatic-testing, self-diagnostic charger: Continuously monitors the unit's status
- Automatically performs battery load testing and auto-cycling at preset intervals
- Indicates malfunctions or auto-test failures
- May accept load to 80% capacity when load feature power factor of 0.9 or more

MECHANICAL

- 18 Gauge steel construction [cabinet B], 16 Gauge steel construction [cabinet C]
- Universal spider knockout pattern and keyhole mounting slots stamped into back of cabinet
- Multiple conduit entry knockouts
- Air intake and exhaust fan placed on the sides for 1 000 W and more
- White powder coat finish standard
- Separate battery compartment

APPROVALS

- CSA certified to C22.2 #141-15

OVERVIEW		
ELECTRICAL	NORMALLY ON AND OFF	120 V AC OR 347 V AC
MECHANICAL	SEPARATE BATTERY COMPARTMENT	STEEL CONSTRUCTION
 		

TYPICAL SPECIFICATION



TYPICAL SPECIFICATION

1. Supply and install The Aimlite EBST-MVP mini-inverter designed to provide power output based on the input voltage, either 120 V AC or 347 V AC. The EBST-MVP features a transfer time of 2 seconds, a momentary push-button test switch, diagnostic LEDs for AC ON and CHARGE indication, a fully automatic current-limited charger, line-latched low voltage protection, and brownout and short circuit protection. The device includes terminal block connectors for output load, standard dimming override control, an auto transfer switch for normally-on lighting circuits, and maintenance-free sealed lead-acid battery(s). The EBST-MVP also incorporates overload protectors and is constructed using steel cabinets with knockout patterns, keyhole mounting slots, multiple conduit entry knockouts, and air intake/exhaust fans for models with 1,000 W and above. The device is finished with a white powder coat and includes a separate battery compartment the EBST-MVP shall be CSA certified to C22.2 #141-15.

2. Electrical Specifications:

- Input Voltage: 120 V AC or 347 V AC
- Output Voltage: 120 V AC or 347 V AC
- Transfer Time: 2 seconds
- Push-Button Test Switch: Momentary type
- Diagnostic LEDs: AC ON and CHARGE indication
- Charger Type: Fully automatic, current-limited
- Protection Features: Line-latched low voltage protection, brownout protection, short circuit protection
- Output Load Connectors: Terminal block connectors
- Dimming Override Control: Standard feature
- Auto Transfer Switch: Included for normally-on lighting circuits
- Battery Type: Maintenance-free, sealed lead-acid
- Overload Protection:
 - 1,000 W Model: Fuse allowing a maximum load of 175 A and board protector with protection up to 1,100 W
 - 1,440 W Model: Fuse allowing a maximum load of 175 A and board protector with protection up to 1,500 W

3. Mechanical Specifications:

- **Cabinet Construction:**
 - Cabinet B: 18 Gauge steel construction
 - Cabinet C: 16 Gauge steel construction
- Mounting Options: Universal spider knock-out pattern and keyhole mounting slots stamped into the back of the cabinet
- Conduit Entry Knockouts: Multiple knock-outs provided
- Air Intake/Exhaust: Side-mounted fans for models with 1,000 W and above
- Finish: Standard white powder coat finish
- Battery Compartment: Separate compartment for battery storage

4. Approvals:

- CSA Certification: Certified to C22.2 #141-15 standards

The Aimlite EBST-MVP shall be model number _____

EBST-MVP

ORDERING GUIDE

EBST-MVP			WHT	/	
SERIES	INPUT VOLTAGE [V AC]	CAPACITY [W]	COLOR	OPTION	
EBST-MVP	A - 120 H- 347	320 - 320 ^{1,3} 500 - 500 ^{1,3} 1 000 - 1 000 ^{1,2} 1 440 - 1 440 ^{1,2}	WHT - WHITE	ATD - AUTO-TEST SELF-DIAGNOSTIC (NON AUDIBLE)	

¹ May accept load to 80% capacity when load feature power factor of 0.9 or more

² May accept the surge peak lighting load of 3 000W for 0.5 seconds for 1 000W and above

³ May accept the surge peak lighting load of 1 200W for 0.5 seconds for 320W and 500W

ACCESSORY

See dimension next page.

PART NO	DESCRIPTION
SHELF001	RIGID 14 GAUGE FREE STANDING SHELF

MODEL RATINGS

MODEL	VOLTS [V DC]	30 MIN.	60 MIN.	90 MIN.	120 MIN.	180 MIN.
EBST-MVP12320	12	320	180	125	110	75
EBST-MVP12500	12	500	280	195	175	125
EBST-MVP121000	12	1000	565	395	350	250
EBST-MVP121440	12	1440	850	595	525	375

WEIGHT

120 V

WATTS [W]	CABINET	WITHOUT BATTERY[S] [LBS]	WITH BATTERY[S] [LBS]
320	CABINET B	29.2	53
500	CABINET B	29.1	71
1 000	CABINET C	61.3	145
1 440	CABINET C	63.4	189


347 V

WATTS [W]	CABINET	WITHOUT BATTERY[S] [LBS]	WITH BATTERY[S] [LBS]
320	CABINET B	41.2	65
500	CABINET B	42.1	84
1 000	CABINET C	98.3	182
1 440	CABINET C	100.4	226


EBST-MVP

DIMENSIONS


CABINET B




SHELF001



CABINET C



EXPLODED VIEW



Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.