

The EXHZ and SXHZ series of hazardous location exit signs is designed to meet and exceed the most stringent code requirements. The housings are made from copper free, heavyduty die cast aluminum. The frame and faceplate(s) are manufactured in heavy gauge steel with a white, powder coating finish. The signs can be specified to suit a variety of mounting options including ceiling, wall and pendant mount.

FEATURES AND SPECIFICATIONS

CIRCUITRY - AC & AC/DC

- LED ultra bright light source
- Input voltages 120/347 V AC
- Emergency back-up votage: 6 V, 12 V or 24 V DC

MECHANICAL

- Die cast, copper free aluminum, white or raw aluminum finish
- Steel exit sign, white powder coat finish standard
- Snap out directional chevrons/arrows
- Wiring pre-pulled through fixture
- Wall and ceiling models c/w integrated die cast junction box
- Junction box c/w oversized integral mounting holes and tapped and plugged rigid holes
- Comes with a transfer panel for hazardous locations (for AC/DC versions)
- TSFN enclosure must be installed/located outside the classified hazardous location
- Temperature code: T6

APPROVALS

- CSA Certified to C22.2 #137
- CSA Certified to C22.2 #141-15
- CSA Certified to C860-11
- Class I, Division 1 & 2, Groups C, D

Project:
Type:
Catalogue #:
Drawn by:
Date:











HAZARDOUS



MOUNTING & DIMENSIONS










CEILING









OVERVIEW

Light source	LED		
Input voltage	120/347 V AC		
DC input voltage	6 V DC, 12 V DC, or 24 V DC		



ORDERING GUIDE

Series	Nbr of faces	Mounting	DC Voltage	Options†
EXHZ - Exit	1 - Single face	C - Ceiling mount	Blank - AC only	SPW - Special wording or graphic
SXHZ - Sortie	2 - Double face	P - Pendant mount	06 - 6 V	
		W - Wall mount	12 - 12 V	
			24 - 24 V	

[†] For detailed options descriptions, please consult the options page.

Comments



All products are subject to change or may be discontinued any time without notice.

