

EXST-B6L

BILINGUAL STEEL SIGN

NRCAN C860 REGISTERED

LED 120/347 VAC INPUT



The EXST-B6L series of commercial steel bilingual exit and sortie signs features a slim profile that eliminates light leaks combined with a simple to install design. Ideal for use in facilities required to meet current bilingual code requirements such as airports or government buildings and institutions. Available in AC only, AC/DC and internally self-powered versions.

FEATURES & SPECIFICATIONS

CIRCUITRY - AC & AC/DC

- LED ultra bright light source
- 120/347 VAC Input, field selectable
- 3.1 W power consumption single or double face
- Emergency DC wattages as follows:
 - 6 VDC = 2.0 W
 - 12 VDC = 3.2 W
 - 24 VDC = 6.7 W

CIRCUITRY - SELF-POWERED

- LED ultra bright light source
- 120/347 VAC Input, field selectable
- 9.0 W power consumption single or double face
- High-performance, sealed Ni-Cad battery
- 90 minutes emergency duration (standard)
- Solid state transfer and battery charger

MECHANICAL

- 20 gauge steel construction
- Slide out faceplates and backplates for rapid and simple installation
- Snap out directional chevrons/arrows
- Universal models include ceiling mount, field installable canopy kit c/w spider plate
- Universal models include ceiling, field installable canopy kit c/w spider plate
- Multiple conduit entry knockouts
- White powder coat finish standard

COMPLIANCE

- CSA Certified to C22.2 #141.15 and C860



Energy Verified
Énergie Vérifiée

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

EXST-B6L

ORDERING GUIDE

SERIES	NBR OF FACES	MOUNTING ¹	COLOR	DC VOLTAGE
EXST B6L 6" (CSA C860 APPROVED HEIGHT)	U- UNIVERSAL FACE	C - CEILING MOUNT	WHT - WHITE	UNVDC - UNIVERSAL DC BACKUP VOLTAGE 6, 12 OR 24VDC SELECTABLE
	1- SINGLE FACE	W - WALL MOUNT		BAT - SELF-POWERED FOR 90 MINUTES

¹ For end mount please refer to EXAL-SXAL.

DIMENSIONS

