

EXWW

« RAINSTORM »

NEMA4X/EEMAC4X

The EXWW series of NEMA4X and EEMAC4X rated weatherproof signs is designed to operate in extreme environments. The fully gasketed housing is suitable for outdoor and wash-down locations. Available in AC/DC and internally self-powered versions.



FEATURES & SPECIFICATIONS

CIRCUITRY - AC & AC/DC

- LED ultra bright light source
- 120/347 V AC Input, field selectable
- 1.9 W power consumption single or double face
- Emergency DC wattages as follows:

UNVDC				
6 V	12 V	24 V	120 V	347 V
1.0 W	1.4 W	3.5 W	1.9 W	1.8 W

BAT	
120 V	347 V
3.1 W	2.9 W

CIRCUITRY - SELF-POWERED

- LED ultra bright light source
- 120/347 V AC Input, field selectable
- 2 W power consumption single or double face
- High-performance, sealed Ni-Cad battery
- 90 minutes emergency duration
- Solid state transfer and battery charger

MECHANICAL

- Heavy-duty glass fibre reinforced polyester construction
- Lens with one piece, molded gasket
- Four integral mounting holes (one per corner) protected behind polycarbonate cover
- Lens secured to housing with four oversized captive screws
- The housing is supplied standard in a grey industrial finish. Face plate standard grey.

COMPLIANCE

- CSA Certified to C22.2 #141-15 and C860



Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

ORDERING GUIDE

EXWW			GRY		
SERIES	NBR OF FACES	MOUNTING	FRAME COLOR	MASK COLOR	DC VOLTAGE*
EXWW	1 - SINGLE FACE 2 - DOUBLE FACE	C - CEILING MOUNT W - WALL MOUNT E - END MOUNT P - PENDANT MOUNT	GRY - GREY	GRY - GREY (STANDARD)	UNVDC - UNIVERSAL DC BACKUP VOLTAGE 6, 12 OR 24 V DC BAT - SELF-POWERED FOR 90 MINUTES

* If AC only is required, select the UNVDC option and do not connect the DC wires when installing.

DIMENSIONS

