

Project: \_\_\_\_\_\_

Type: \_\_\_\_\_

Catalogue #: \_\_\_\_\_

Drawn by: \_\_\_\_\_

Date: \_\_\_\_

The EXZN2 series of Class I, Division 2 rated exits is designed to perform in demanding hazardous applications. The unit maintains its sealed interior with a continuous integral gasket. As well any LED pilot light or test switch are sealed type.

### **FEATURES AND SPECIFICATIONS**

### **ELECTRICAL - AC/DC**

- LED ultra bright light source
- 120/347VAC Input, field selectable
- 2.8W power consumption single face
- Emergency DC wattages as follows:6VDC = 1.9W 12VDC = 2.9W 24VDC = 7W

### **CIRCUITRY - SELF-POWERED**

- LED ultra bright light source
- 120/347VAC Input, field selectable
- $-\ 9.5W$  power consumption Single face
- High-performance, sealed Ni-Cad battery
- 90 minutes emergency duration (standard)
- Solid state transfer and battery charger

#### **MECHANICAL**

- Heavy-duty non-metallic, reinforced construction
- One piece, molded and gasketed lens
- Removable directional chevrons/arrows
- Bottom hinged cover secured with two screws
- One-way breather valve for release of gases and/ or moisture condensation
- All external metal hardware is stainless steel and steel screws
- Single face, wall mount only
- Grey finish housing, white faceplate standard

### **APPROVALS**

- CSA Certified to C22.2 #137
- CSA Certified to C22.2 #141-15
- CSA Certified to C860-11
- Class I, Division 2, Groups C, D



(self powered version)











# DIMENSIONS





### **OVERVIEW**

Light source	LED
Input voltage	120/347V AC
Input power	2.8W AC/DC single face 9.5W self-powered single face
DC voltage & power	6V DC = 1.9W 12V DC = 2.9W 24V DC = 7W



## **ORDERING GUIDE**

EXZN2	1	GRY -		
Series	Nbr of faces	Colour	Operation	
EXZN2	1 - Single face	GRY - Grey	,	
			<b>BAT -</b> Self-powered for 90 minutes	

## **TEMPERATURE CODES**

	25°C	40°C
UNVDC	T6	T6
BAT	T6	T5

## Comments

All products are subject to change or may be discontinued any time without notice.

