Proiect		
*		
Cotologue nº		





OVA-L OUTDOOR DECORATIVE LED WALL PACK

The OVA-L is a decorative outdoor LED wall luminaire. Its modern design made of sturdy die cast aluminum is a great combination of aesthetics and durability. The highly efficient LEDs maximize the lumen output while minimizing wattage consumption. The OVA-L is intended for use in commercial or residential areas. Typical applications include general lighting of parking areas, parks, underground pathways, hotels and entry-ways. Wall mount directly over an octagon box or use with surface conduit.



FEATURES & SPECIFICATIONS

INTEGRATED PHOTOCELL

CONSTRUCTION

Housing

- Die cast aluminum housing
- Available in Black

Installation

Wall mount or surface conduit

Lens

Polycarbonate lens

ELECTRICAL

- Integrated photocell: Easily select photocell mode or wall switch mode
- Input voltage: 120 V
- High quality, long life LEDs
- Estimated lifespan of 50 000 hours

COMPLIANCES

- · Suitable for wet locations
- · cULus Listed

OVERVIEW			
LIGHT SOURCE	LED	EFFICIENCY (LM/W)	85.1
WATTS (W)	14	COLOR TEMPERATURE (K)	5 000
LUMEN OUTPUT (LM)	1 192		







QUICKSHIP





Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.



OVA-L • REV. 2024-10-9 T 514 227-1288 TF 1 866 348-2374 aimlite.com




QUICK SHIP ORDERING GUIDE



PART NO	VOLTS	WATTS	LUMEN OUTPUT	COLOR TEMP.	EFFICIENCY	HOUSING	ne THD	BUG	L70	TM21	LM80	
PARTNU	(V)	(W)	(LM)	(K)	[LM/W]	COLOR	FF	[%]	506	(HRS)	(HRS)	(HRS)
OVA-LA1-4/50K/P-BK	120	14	1 192	5 000	85.1	BLACK	0.99	8.40	021	>33 000	50000	6000

QUICK SHIP: Product availability is subject to change without notice. Please contact your AimLite customer service representative to confirm inventory levels at time of order.

DIMENSIONS





TF 1866 348-2374