

# VP4T8332

## VAPOUR TIGHT FLUORESCENT

### 3 LAMPS



The Aimlite VP4T8332 sealed 4 foot linear fluorescent luminaire is ideal for a variety of industrial, commercial applications. It can be installed inside or outside.

## FEATURES & SPECIFICATIONS

### CONSTRUCTION

#### Housing

- The housing is sealed with a uniform gasket that blocks the ingress of moisture and dust and reinforced snap clips lock the luminaire together
- Polycarbonate construction makes the luminaire lightweight, flexible and highly impact resistant
- The UV stabilized polycarbonate housing and lens are impervious to rust or rot and are unaffected by extreme temperatures

#### Mounting options

- The housing is moulded with a recessed conduit knockout at either end along with row mounting, end aligners
- A sealed, plastic cable gland and stainless steel mounting hardware are included with each luminaire
- Can be surface wall, ceiling mounted or suspended with supplied clips

#### Reflector



- The VP4T8332 specular reflector provides superior light distribution for maximum light output.

### BALLAST

- Our fixtures come standard with electronic instant start ballasts (not intended for use with occupancy sensors).

### COMPLIANCES

- Suitable for wet and damp locations
- IP65
- CSA certified luminaire
- Flame spread rating FSR85
- Smoke classification SDC430

OVERVIEW	
LIGHT SOURCE	FLUORESCENT
WATTS [W]	32
LAMP TYPE	T8
<div>   FLUORESCENT            WET LOCATION            IP65 RATING            </div>	

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

# VP4T8332

## ORDERING GUIDE

VP4	T8	3	32	AC	120
SERIES	LAMP TYPE	NBR OF LAMPS	WATTAGE [W]	OPERATION	VOLTS [VAC]
VP4	T8	3 - 3	32 - 32	AC - AC ONLY [STANDARD]	120 - 120

## DIMENSIONS

