



LPDL™ CCT Selectable Gen. 2 LED Low Profile Downlight

The LPDL CCT Selectable Gen. 2 series is perfect for any type of residential application where an even light output is desired. It is easy to select the right color temperature to fit the ambiance of a space with the switch conveniently located on the back of the LED module. Featuring an airtight construction and IC rating, this downlight series is suitable for installation in all types of ceilings.



dimable



wet
location



■ Color Selectable

An all-in-one LED downlight solution offering ultimate versatility, with the ability to change the color temperature (2 700/3 000/3 500/ 4 000/5 000 K). An ideal solution for reducing stocking inventory.

■ FT6 Cable Rating

The FT6 rated cable allows this LED downlight with remote driver to be installed in plenum ceilings. Perfect for commercial buildings as well as residential environments.

■ Less Than 1" Thick

This ultra slim recessed downlight is designed to be easily installed in shallow or constraint areas such as wood beams, ceiling joist or air ducts.

Offering variety of finish and size to complete your project!


- Easy and quick installation with spring clips

- Available in 3", 4" and 6"

- 90+ CRI for true color accuracy

- Frosted polycarbonate lens providing 110° beam angle

- CCT selectable switch is located on the back of LED module



- Air tight and IC rated for direct contact with insulation

Trim Variety

Available in white and black

3"



4"




6"



Compatible accessories

Select a variety of accessories for different installation options!

Adjustable mounting plate



Mounting plate with hanger bars



Square mounting plate



Goof rings



6' FT6 Extension cord



Vapor barrier extender

