



## SINGLE RING CCT SELECTABLE LED Ceiling Luminaire

Available in different sizes, our Single Ring LED Ceiling Luminaire series is an excellent choice to add a decorative touch to any residential or commercial applications such as hallways, bedrooms, offices and more!



### ■ Color Selectable

Versatile solution with an integrated 5 color temperature selection (2 700/3 000/3 500/4 000/5 000 K). Easily select the desired color temperature using the switch located inside the housing. An ideal solution for reducing stocking inventory.

### ■ Accentuate any space

With a Brushed Nickel decorative ring our Single Ring luminaires will help accentuate any residential or commercial space.

### ■ Easily installed

Appreciate an easy installation and maintenance, with a lens that is easily removable.

## Adapt the color temperature to your needs!

- Available in 12" and 14" with a slight uplight effect

- Steel housing with a decorative ring in brushed nickel finish

- Polystyrene frosted lens for a uniform light distribution



- CCT switch is placed discreetly inside the housing on LED board, easily accessible simply remove the lens





# Specification Table

Order code	Model number	Watts (W)	Volts (VAC)	Color temp. (K) <sup>1</sup>	Lumen output (lm) <sup>2,3</sup>	Efficiency (lm/W)	CRI	Life L70 (hrs) <sup>4</sup>	Beam angle (°)	Shape	Finish	Dimming (Yes/No)	Power factor	Master case qty
5 CCT Selectable														
12"														
68929	CLSR12-R15W-A-5CBN	15	120	2 700/3 000/3 500/4 000/5 000	1 266	89	80+	50 000	120	Round	Brushed nickel	Yes	≥0.90	4
14"														
68930	CLSR14-R25W-A-5CBN	25	120	2 700/3 000/3 500/4 000/5 000	1 940	80	80+	50 000	120	Round	Brushed nickel	Yes	≥0.90	4

<sup>1</sup> Typical color temperature range: +/- 5 %.

<sup>2</sup> Lumen values are derived from Energy Star reported data. Initial lumens range: +/- 10 %.

<sup>4</sup> Life hours are derived from IESNA LM-80-08 testing report and projected per IESNA TM-21-11 extrapolations.

# Compatible accessories

Order code	Model number	Type	Finish	Diameter (in)	Compatible with	Master case qty
68932	LEN-CLSR12-BN	Lens	Frosted	11 3/4"	68929	10
68933	LEN-CLSR14-BN	Lens	Frosted	13 5/8"	68930	10

