

Choose the right LED Downlight

All of our LED downlights are available in quick ship and certified Energy Star.

		LPDL - Low profile downlight				Swivel Gen. 2	Gimbal	CIELO	Stellar	Retro Gen. 2	COMETO Fire-rated	COMETO Commercial	CDU Gen. 2
		Regressed	Stanpro	Choice	Eco Choice	Choice						Choice	
Main selling features		Glare-free design for enhanced illuminance	Variety of sizes and colors	Quality-Price	Economical solution	Directional downlight which can highlight specific zones with 360° rotation and up to 90° tilt	Outstanding performance, small aperture and regressed design with directional light output	Trimless downlight for a clean and seamless finish	Small aperture and sleek design	Retrofit solution with E26 screw-in adaptor for existing recessed cans, easy installation	Slim backlit downlight, designed and tested to meet fire-resistance standards.	Slim backlit commercial downlight with 5 CCT and 3 power selectables	All-in-one commercial downlight with integrated 3 CCT and 3 power selectable
Size(s) (in)		4, 6	3, 4, 6	4, 6	4	4, 6	3.5	3	2	4, 5-6	4, 6	4, 6, 8	4, 6, 8
Shape													
Watts (W)		9, 12	7, 7.5, 12	9, 12	9	9, 13	12	12, 15	12	10, 15	11, 12	8/10/12 12/15/18 18/20/25	7/9/12 12/16/20 15/20/25
Lumen output (lm)		750, 1 200	580, 620, 1 000	800, 1 050	750	805, 1 210	Warm Dim : 660 Single CCT : Up to 950 CCT Selectable : 850	1 100, 1 250	Warm Dim : 850 CCT Selectable : 1 000	820, 1 250	750, 1 000	750/900/1 000 1 200/1 500/1 800 1 700/2 200/2 800	595/765/1 000 1 080/1 440/2 000 1 800/2 200/2 900
Volts (VAC)		120	120	120	120	120	120 120-277 ²	120	120	120	120	120-347	120-347
Color Temp. (K)	Single						3 000, 4 000						
	Warm Dim						3 000-2 200		3 000-2 200				
	Selectable	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	5 CCT : 2 700/3 000/3 500/4 000/5 000	3 CCT : 3 000/3 500/4 000
Color finish													
CRI		90+	90+	90+	80+	90+	90+	90+	90+	90+	80+	80+	80+
Beam angle													
Location													
Dimmable		ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	0-10 V ²	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	0-10 V	0-10 V
Cable rated		FT4	FT6	FT4	FT4	FT4	FT6	FT6	FT6		FT6	FT6	
Warranty (year)		5	7	5	3	5	5	5	5	5	5	5	5
IC rated		✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓
Airtight		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Other details							Available in individual bulk pack of 10 drivers and 10 LED modules for 2-phases job site deliveries ³	Available in two styles: Gimbal and Zoomable	Interchangeable Black trim ⁴		2-hour fire-resistant steel housing		

¹ Only available with 5CCT selectable LED module

² Only available with bulk pack option

³ Only available in 3.5" 30K white

⁴ Sold separately