

General Service

Order code	Description	Watts (W)	Base	Volts (V)	Lumens at 120 V (lm)	Average life (hrs)	Filament type	Finish/ Color	Case qty (inner/master)
A15									
MOL : 3 1/2 in. (89 mm) LCL : 2 3/8 in. (60 mm)									
50125	15A15/CL/5M/130V/STD	15	E26	130	85	5 000	C-9	Clear	6/60
50166	15A15/F/5M/130V/STD	15	E26	130	80	5 000	C-9	Frost	6/60
50145	25A15/CL/5M/130V/STD	25	E26	130	135	5 000	C-9	Clear	6/60
50126	25A15/F/5M/130V/STD	25	E26	130	135	5 000	C-9	Frost	6/60
A19									
MOL : 4 1/4 in. (108 mm) LCL : 3 1/8 in. (79 mm)									
50941	15A19/CL/6M/130V/STD	15	E26	130	80	6 000	C-9	Clear	6/120
50931	25A19/CL/1M/120V/STD/4P	25	E26	120	150	1 000	C-9	Clear	6/120
B8									
MOL : 3 5/32 in. (80 mm) LCL : 1 7/8 in. (48 mm)									
50635	15B8/F/2.5M/E12/130V/STD	15	E12	130	70	2 500	C-7A	Frost	6/120
50639	25B8/F/2.5M/E12/130V/STD	25	E12	130	115	2 500	C-7A	Frost	6/120
B10									
MOL : 3 29/32 in. (99 mm) LCL : 1 25/32 in. (45 mm)									
50611	15B10/CL/3M/E12/130V/STD	15	E12	130	75	3 000	C-7A	Clear	6/120
50543	25B10/CL/3M/E12/130V/STD	25	E12	130	165	3 000	CC-2V	Clear	6/120
50612	25B10/F/3M/E12/130V/STD	25	E12	130	165	3 000	CC-2V	Frost	6/120
MOL : 3 1/2 in. (89 mm) LCL : 2 1/8 in. (54 mm)									
50621	25B10/CL/3M/130V/STD	25	E26	130	165	3 000	CC-2V	Clear	6/120
MOL : 3 31/32 in. (101 mm) LCL : 1 25/32 in. (45 mm)									
50548	25B10/CL/3M/E14/130V/STD	25	E14	130	165	3 000	CC-2V	Clear	6/120
B10 Suitable for base up									
MOL : 3 1/2 in. (89 mm) LCL : 2 1/8 in. (54 mm)									
50624	25B10/F/3M/130V/STD	25	E26	130	165	3 000	CC-2V	Frost	6/120
50622	40B10/CL/3M/130V/STD	40	E26	130	280	3 000	CC-2V	Clear	6/120
50625	40B10/F/3M/130V/STD	40	E26	130	280	3 000	CC-2V	Frost	6/120
MOL : 3 29/32 in. (99 mm) LCL : 1 25/32 in. (45 mm)									
50544	40B10/CL/3M/E12/130V/STD	40	E12	130	280	3 000	CC-2V	Clear	6/120
50613	40B10/F/3M/E12/130V/STD	40	E12	130	280	3 000	CC-2V	Frost	6/120
50545	60B10/CL/3M/E12/130V/STD	60	E12	130	430	3 000	C-7A/3	Clear	6/120
50614	60B10/F/3M/E12/130V/STD	60	E12	130	430	3 000	C-7A/3	Frost	6/120
MOL : 3 31/32 in. (101 mm) LCL : 1 25/32 in. (45 mm)									
50549	40B10/CL/3M/E14/130V/STD	40	E14	130	280	3 000	CC-2V	Clear	6/120
50552	40B10/F/3M/E14/130V/STD	40	E14	130	280	3 000	CC-2V	Frost	6/120
50550	60B10/CL/3M/E14/130V/STD	60	E14	130	430	3 000	C-7A/3	Clear	6/120
50553	60B10/F/3M/E14/130V/STD	60	E14	130	430	3 000	C-7A/3	Frost	6/120
BR30									
MOL : 5 1/8 in. (130 mm) LCL : 3 11/32 in. (85 mm)									
50219	50BR30/FL/5M/130V/STD	50	E26	130	240	5 000	C-9	Frost	6/60
50077	65BR30/FL/5M/ES/130V/STD	65	E26	130	470	5 000	CC-6	Frost	6/60
BR40									
MOL : 6 9/16 in. (167 mm) LCL : 4 1/4 in. (108 mm)									
50080 ¹	65BR40/FL/5M/ES/130V/STD	65	E26	130	470	5 000	CC-6	Clear	1/12
C7									
MOL : 2 1/8 in. (54 mm) LCL : 1 1/2 in. (38 mm)									
50308	7C7/CL/3M/E12/125V/STD 10P	7	E12	125	26	3 000	C-7A	Clear	10/500

¹ This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

Incandescent Lamps

Order code	Description	Watts (W)	Base	Volts (V)	Lumens at 120 V (lm)	Average life (hrs)	Filament type	Finish	Case qty (inner/master)
CA4.5									
MOL : 2 3/4 in. (70 mm) LCL : 1 5/8 in. (41 mm)									
52153	10CA4.5/CL/2M/E12/130V/STD	10	E12	130	40	2 000	C-7A	Clear	6/120
CA8									
MOL : 3 19/32 in. (91 mm) LCL : 1 25/32 in. (45 mm)									
52157	10CA8/F/2.5M/E12/130V/STD	10	E12	130	50	2 500	C-7A	Frost	25/500
50641	15CA8/CL/2.5M/E12/130V/STD	15	E12	130	70	2 500	C-7A	Clear	6/120
10269	15CA8/F/2.5M/E12/130V/STD	15	E12	130	70	2 500	C-7A	Frost	25/500
50643	25CA8/F/2.5M/E12/130V/STD	25	E12	130	115	2 500	C-7A	Frost	6/120
50642	40CA8/CL/2.5M/E12/130V/STD	40	E12	130	215	2 500	C-7A	Clear	25/500
50644	40CA8/F/2.5M/E12/130V/STD	40	E12	130	215	2 500	C-7A	Frost	25/500
CA10									
MOL : 3 29/32 in. (99 mm) LCL : 2 1/8 in. (54 mm)									
51051	25CA10/CL/3M/130V/STD	25	E26	130	120	3 000	C-7A	Clear	6/120
50629	25CA10/F/3M/130V/STD	25	E26	130	115	3 000	C-7A	Frost	6/120
MOL : 4 3/32 in. (104 mm) LCL : 1 7/8 in. (48 mm)									
50615	25CA10/CL/3M/E12/130V/STD	25	E12	130	135	3 000	CC-2V	Clear	6/120
50618	25CA10/F/3M/E12/130V/STD	25	E12	130	115	3 000	CC-2V	Frost	6/120
50616	40CA10/CL/3M/E12/130V/STD	40	E12	130	235	3 000	CC-2V	Clear	6/120
50619	40CA10/F/3M/E12/130V/STD	40	E12	130	205	3 000	CC-2V	Frost	6/120
50617	60CA10/CL/3M/E12/130V/STD	60	E12	130	455	3 000	CC-2V	Clear	6/120
50620	60CA10/F/3M/E12/130V/STD	60	E12	130	450	3 000	CC-2V	Frost	6/120
F15									
MOL : 4 1/2 in. (115 mm) LCL : 2 9/16 in. (65 mm)									
69853	40F15/CL/1.5M/130V/STD S2	40	E26	130	305	1 500	CC-6	Clear	6/24
G9.5									
MOL : 2 1/16 in. (52 mm) LCL : 1 1/2 in. (38 mm)									
52165	7.5G9.5/CL/1M/E12/130V/STD	7	E12	130	40	1 000	C-7A	Clear	25/500
G11									
MOL : 2 5/16 in. (59 mm) LCL : 1 5/8 in. (41 mm)									
69785	7.5G11/CL/1M/E12/130V/STD S2	7.5	E12	130	40	1 000	C-7A/3	Clear	6/120
69787	7.5G11/CL/1M/130V/STD S2	7.5	E26	130	40	1 000	C-7A/3	Clear	6/120
G13									
MOL : 2 3/8 in. (60.5 mm) LCL : 1 11/16 in. (43 mm)									
50681	10G13/CL/3M/E12/130V/STD	10	E12	130	50	3 000	C-7A	Clear	25/500
50682	25G13/CL/3M/E12/130V/STD	25	E12	130	135	3 000	CC-2V	Clear	6/120
G16.5									
MOL : 3 in. (76 mm) LCL : 1 7/8 in. (48 mm)									
10334	5G16.5/CL/3M/E12/130V/STD	5	E12	130	20	3 000	C-7A	Clear	6/120
10268	10G16.5/CL/3M/E12/130V/STD	10	E12	130	50	3 000	C-7A	Clear	6/120
50660	15G16.5/CL/3M/E12/130V/STD	15	E12	130	70	3 000	C-7A	Clear	6/120
50662	15G16.5/WH/3M/E12/130V/STD	15	E12	130	60	3 000	C-7A	White	6/120
50652	25G16.5/WH/3M/E12/130V/STD	25	E12	130	120	3 000	CC-2V	White	6/120
52453	25G16.5/CL/3M/E12/130V/ELUME 2P	25	E12	130	160	3 000	C-7A	Clear	24/120
50777	25G16.5/CL/3M/E14/130V/STD	25	E14	130	160	3 000	CC-6	Clear	6/120
50649	25G16.5/CL/3M/130V/STD	25	E26	130	135	3 000	CC-2V	Clear	6/120
50653	25G16.5/WH/3M/130V/STD	25	E26	130	120	3 000	CC-2V	White	6/120
50654	40G16.5/WH/3M/E12/130V/STD	40	E12	130	230	3 000	CC-2V	White	6/120
52454	40G16.5/CL/3M/E12/130V/ELUME 2P	40	E12	130	160	3 000	C-7A	Clear	24/120
50651	40G16.5/CL/3M/130V/STD	40	E26	130	250	3 000	CC-2V	Clear	6/120
50655	40G16.5/WH/3M/130V/STD	40	E26	130	230	3 000	CC-2V	White	6/120
50656	60G16.5/CL/3M/E12/130V/STD	60	E12	130	440	3 000	CC-2V	Clear	6/120
50658	60G16.5/WH/3M/E12/130V/STD	60	E12	130	400	3 000	CC-2V	White	6/120

Order code	Description	Watts (W)	Base	Volts (V)	Lumens at 120 V (lm)	Average life (hrs)	Filament type	Finish	Case qty (inner/master)
G16.5 (cont.)									
MOL : 2 7/8 in. (73 mm) LCL : 2 1/16 in. (52 mm)									
50779	25G16.5/WH/3M/E14/130V/STD	25	E14	130	150	3 000	CC-6	White	25/500
50782	60G16.5/WH/3M/E14/130V/STD	60	E14	130	580	3 000	CC-6	White	25/500
G25									
MOL : 2 1/2 in. (114 mm) LCL : 3 1/32 in. (77 mm)									
50199	25G25/CL/3M/130V/STD	25	E26	130	135	3 000	C-9	Clear	6/60
50196	25G25/WH/3M/130V/STD	25	E26	130	115	3 000	C-9	White	6/60
50222	40G25/CL/3M/130V/STD	40	E26	130	255	3 000	C-9	Clear	6/60
50155	40G25/WH/3M/130V/STD	40	E26	130	230	3 000	C-9	White	6/60
G30									
MOL : 5 13/32 in. (137 mm) LCL : 3 9/32 in. (83 mm)									
50203	25G30/CL/3M/130V/STD	25	E26	130	115	3 000	C-9	Clear	6/60
50204	40G30/CL/3M/130V/STD	40	E26	130	230	3 000	C-9	Clear	6/60
50202	40G30/WH/3M/130V/STD	40	E26	130	215	3 000	C-9	White	6/60
G40									
MOL : 6 15/16 in. (176 mm) LCL : 3 29/32 in. (99 mm)									
50205	25G40/CL/3M/130V/STD	25	E26	130	100	3 000	C-9	Clear	6/12
50150	40G40/WH/3M/130V/STD	40	E26	130	215	3 000	C-9	White	6/12
50210	100G40/WH/3M/130V/STD	100	E26	130	820	3 000	C-9	White	6/12
50112	150G40/WH/3M/130V/STD	150	E26	130	1 175	3 000	C-9	White	6/12
PS25									
MOL : 6 15/16 in. (176 mm) LCL : 5 1/32 in. (128 mm)									
50071	300PS25/CL/5M/130V/STD	300	E26	130	2 725	5 000	C-9	Clear	6/24
50088	300PS25/F/5M/130V/STD	300	E26	130	2 725	5 000	C-9	Frost	6/24
PS35									
MOL : 9 13/32 in. (239 mm) LCL : 6 1/2 in. (165 mm)									
50225	300PS35/CL/5M/E39/130V/STD	300	E39	130	2 725	5 000	C-9	Clear	6/24
R14									
MOL : 2 1/8 in. (54 mm) LCL : 1 21/32 in. (42 mm)									
50665	25R14/FL/1.5M/120V/STD	25	E26	120	150	1 500	CC-2V	Clear	6/120
50663	40R14/F/FL/1.5M/120V/STD	40	E26	120	280	1 500	CC-2V	Frost	6/120
MOL : 2 9/16 in. (65 mm) LCL : 1 31/32 in. (50 mm)									
50666	25R14/FL/1.5M/E17/120V/STD	25	E17	120	150	1 500	CC-2V	Frost	6/120
R16									
MOL : 3 1/2 in. (89 mm)									
52168	25R16/SF/1.5M/E12/130V/STD	25	E12	130	120	3 000	CC-2V	Frost	25/500
52459	40R16/SW/1M/120V/ELUME 2P	40	E26	120	445	1 000	CC-6	Soft white	12/60
52460	60R16/SW/1M/130V/ELUME 2P	60	E26	130	730	1 000	CC-6	Soft white	12/60
R19									
MOL : 3 31/32 in. (101 mm) LCL : 3 1/32 in. (77 mm)									
50136	40R19/SW/1.5M/120V/STD	40	E26	120	320	1 500	CC-6	Soft white	6/60
R20									
MOL : 3 29/32 in. (99 mm) LCL : 2 15/16 in. (75 mm)									
50211	30R20/SP/5M/130V/STD	30	E26	130	145	5 000	C-9	Clear	6/60
61707	45R20/FL/5M/130V/ELUME 2P	45	E26	130	242	5 000	CC-7	Frost	6/60
61705	45R20/SP/5M/130V/STD	45	E26	130	242	5 000	CC-6	Frost	6/60

Incandescent Lamps

Order code	Description	Watts (W)	Base	Volts (V)	Lumens at 120 V (lm)	Average life (hrs)	Filament type	Finish/ Color	Case qty (inner/master)
S11									
MOL : 2 5/16 in. (59 mm) LCL : 1 1/2 in. (38 mm)									
50789	5S11/CL/1M/E17/130V/STD	5	E17	130	25	1 000	C-7A	Clear	25/500
50143	10S11/CL/1M/E17/130V/STD	10	E17	130	60	1 000	C-7A	Clear	6/120
50786	25S11/CL/1M/E17/130V/STD	25	E17	130	130	1 000	C-7A	Clear	25/500
50123	40S11/CL/1M/E17/130V/STD	40	E17	130	275	1 000	C-7A	Clear	6/120
S14									
MOL : 2 5/16 in. (59 mm) LCL : 1 1/2 in. (38 mm)									
59542	11S14/CL/8M/130V/STD	11	E26	130	40	8 000	C-9	Clear	6/24
50147	11S14/CL/3M/130V/STD	11	E26	130	72	3 000	C-9	Clear	25/500
T6									
MOL : 3 1/16 in. (78 mm) LCL : 1 9/16 in. (40 mm)									
50667	15T6/CL/7.5M/E12/130V/STD	15	E12	130	75	7 500	C-5A	Clear	12/120
50668	15T6/CL/7.5M/E12/145V/STD	15	E12	145	90	7 500	C-5A	Clear	12/120
50675	15T6/CL/5M/E17/130V/STD	15	E17	130	70	5 000	C-5A	Clear	12/120
50676	15T6/CL/7.5M/E17/145V/STD	15	E17	145	90	7 500	C-5A	Clear	12/120
T6.5									
MOL : 5 13/32 in. (137 mm) LCL : 3 5/32 in. (80 mm)									
51052	20T6.5/CL/5M/BA15d/130V/STD	20	BA15d	130	115	5 000	C-8	Clear	25/500
50679	20T6.5/F/5M/BA15d/130V/STD	20	BA15d	130	115	5 000	C-8	Frost	12/120
51056	25T6.5/CL/5M/BA15d/125V/STD	25	BA15d	125	180	5 000	C-8	Clear	25/500
50729	25T6.5/F/7.5M/BA15d/145V/STD	25	BA15d	145	145	7 500	C-8	Frost	25/500
50672	25T6.5/CL/7.5M/E12/145V/STD	25	E12	145	180	7 500	C-8	Clear	12/120
50669	25T6.5/CL/5M/E17/130V/STD	25	E17	130	135	5 000	C-8	Clear	12/120
50670	25T6.5/CL/7.5M/E17/145V/STD	25	E17	145	180	7 500	C-8	Clear	12/120
50673	25T6.5/F/7.5M/E17/145V/STD	25	E17	145	180	7 500	C-8	Frost	25/500
T7									
MOL : 2 5/16 in. (59 mm) LCL : 1 5/16 in. (33 mm)									
52195	15T7/CL/1.5M/BA15d/120V/STD	15	BA15d	120	100	1 500	C-7A	Clear	25/1 000
52201	25T7/CL/1.5M/E12/130V/STD	25	E12	130	115	1 500	C-7A	Clear	25/1 000
T8									
MOL : 2 9/16 in. (65 mm) LCL : 1 5/8 in. (41 mm)									
52198	25T8/CL/1.5M/BA15d/120V/STD	25	BA15d	120	220	1 500	C-7A	Clear	25/1 000
69795	25T8/CL/1.5M/E12/120V/STD	25	E12	120	220	1 500	C-5A	Clear	12/120
52197	25T8/CL/1.5M/E17/120V/STD	25	E17	120	220	1 500	C-7A	Clear	25/1 000
T10									
MOL : 5 in. (127 mm) LCL : 2 3/4 in. (70 mm)									
50925	25T10/CL/3M/130V/STD	25	E26	130	135	3 000	C-5V	Clear	6/120
50928	25T10/F/3M/130V/STD	25	E26	130	135	3 000	C-5V	Frost	6/120
50926	40T10/CL/3M/130V/STD	40	E26	130	195	3 000	C-5V	Clear	6/120
50929	40T10/F/3M/130V/STD	40	E26	130	195	3 000	C-5V	Frost	6/120
T10 HO									
MOL : 5 13/32 in. (137 mm) LCL : 3 11/32 in. (85 mm)									
50129	40T10/CL/3M/HO/130V/STD	40	E26	130	300	3 000	C-8	Clear	6/120