

Half-mirror




MOL : 4 1/4 in. (108 mm)
LCL : 3 1/8 in. (79 mm)

A19



MOL : 2 7/8 in. (73 mm)
LCL : 1 7/8 in. (48 mm)

G16.5



MOL : 4 1/2 in. (114 mm)
LCL : 3 1/32 in. (77 mm)

G25



MOL : 5 5/16 in. (135 mm)
LCL : 3 5/8 in. (92 mm)

G30



MOL : 5 13/32 in. (137 mm)
LCL : 3 9/32 in. (83 mm)

G40

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Filament type	Color	Case qty (inner/master)
A19									
52019	60A19/SLV/3M/HM/130V/STD	60	E26	130	N/A	3 000	C-9	Silver	6/120
52020	100A19/SLV/3M/HM/130V/STD	100	E26	130	N/A	3 000	C-9	Silver	24/120
G16.5									
52159	25G16.5/SLV/3M/HM/E12/120V/STD	25	E12	120	N/A	3 000	C-7A	Silver	25/500
52160	40G16.5/SLV/3M/HM/E12/120V/STD	40	E12	120	N/A	3 000	C-7A	Silver	25/500
G25									
52058	25G25/SLV/3M/HM/130V/STD	25	E26	130	N/A	3 000	C-9	Silver	6/60
G30									
51160	60G30/SLV/3M/HM/130V/STD	60	E26	130	N/A	3 000	C-9	Silver	10/100
G40									
14502	60G40/SLV/2.5M/HM/130V	60	E26	130	N/A	2 500	C-9	Silver	6/24
14503	100G40/SLV/2.5M/HM/130V	100	E26	130	N/A	2 500	C-9	Silver	6/24

Krypton & Daylight



Order code	Description	Watts (W)	Base	Volts (V)	Lumens output (lm)	Average life (hrs)	Filament type	Finish	Case qty (inner/master)
Krypton									
A21									
14595	135A21/CL/8M/ES/K/130V	135	E26	130	1 585	8 000	C-9	Clear	24 / 120
G11									
14531	25G11/CL/3M/K/E12/120V	25	E12	120	300	3 000	CC-2V	Clear	10/120
A19 Daylight									
14638	25A19/DL/5M/130V/STD	25	E26	130	N/A	5 000	C-9	Daylight	24/120

¹ This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.

Infrared & Appliance



MOL : 6 9/16 in. (167 mm)
LCL : 4 1/4 in. (108 mm)

BR40



MOL : 6 9/16 in. (167 mm)
MOL : 7 1/4 in. (184 mm)
LCL : 3 29/32 in. (99 mm)

R40



MOL : 3 3/8 in. (86 mm)
LCL : 2 7/16 in. (62 mm)

A15

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Filament type	Finish	Case qty (inner/master)
Infrared BR40									
10251	250BR40/IR/CL/5M/120 130V/STD	250	E26	120	2 400	5 000	C-9	Clear	1/12
R40									
10252	250R40/IR/R/5M/120 130V/STD	250	E26	120	N/A	5 000	C-9	Red	1/12
62561	375R40/IR/CL/5M/120V/STD	375	E26	120	N/A	5 000	C11-3	Clear	1/12
A15 Appliance (Up to 280°C / 535°F)									
67721	40A15/CL/5M/APPL/130V/STD	40	E26	130	350	5 000	C-9	Clear	6/60
67722	40A15/FR/5M/APPL/130V/STD	40	E26	130	320	5 000	C-9	Frost	6/60

Flashing, BLB & Bug



MOL : 4 21/32 in. (118 mm)

G25



MOL : 4 1/4 in. (108 mm)
LCL : 3 1/32 in. (77 mm)

A19



MOL : 4 1/4 in. (108 mm)
LCL : 3 1/32 in. (77 mm)

A19



MOL : 6 15/16 in. (176 mm)
LCL : 3 29/32 in. (99 mm)

G40

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Filament type	Finish/Color	Case qty (inner/master)
Flashing									
G25									
52203	XFLASH/CL/120V	1	E26	120	1 040	10 000 000 flashes	C-11V	Clear	1/50
52205	XFLASH/G/120V	1	E26	120	N/A	10 000 000 flashes	C-9	Green	1/50
Black light blue (BLB)									
A19									
52016	75A19/BLB/1.5M/120V/STD	75	E26	120	N/A	1 500	C-9	Black light blue	6/120
Bug light - 2 pack									
A19									
50153	60A19/CY/6M/BG/130V/STD/2P	60	E26	130	N/A	6 000	C-9	Ceramic yellow	12/120
G40									
52056	60G40/CY/3M/BG/130V/STD	60	E26	130	N/A	3 000	C-9	Ceramic yellow	1/24

Mining



R40

Order code	Description	Watts (W)	Base	Volts (V)	Lumens at 120 V (lm)	Average life at 120 V (hrs)	Filament type	Finish	Case qty (inner/master)
Mining Service									
R40									
50482	300R40/FL/5M/MN/130V/STD	300	E26	130	2 271	5 000	CC-6	Clear	1/12

Trilight



A21



PS25

Order code	Description	Watts (W)	Base	Volts (V)	Lumens at 120 V (lm)	Average life at 120 V (hrs)	Filament type	Finish	Case qty (inner/master)
A21									
50117	50/150A21/WH/4M/130V/STD	50 / 100 / 150	E26d	130	395 / 910 / 1300	4 000	CC-8	White	6/24
51159	50/250A21/WH/2M/120V/STD	50 / 200 / 250	E26d	120	400 / 2 200 / 2 600	2 000	CC-8	White	6/24
PS25									
51123	100/300/PS25/WH/E39/130V/STD	100 / 200 / 300	E39d	130	910 / 1 815 / 2 725	2 500	CC-6	White	6/24

Long life



MOL : 4 1/4 in. (108 mm)
LCL : 3 1/32 in. (77 mm)

A19



MOL : 5 5/16 in. (135 mm)
LCL : 3 1/2 in. (89 mm)

A21



MOL : 4 1/2 in. (114 mm)
LCL : 2 7/8 in. (73 mm)

G25



MOL : 6 15/16 in. (176 mm)
LCL : 4 3/8 in. (111 mm)

G40



MOL : 3 29/32 in. (99 mm)
LCL : 2 15/16 in. (75 mm)

R20



MOL : 3 1/2 in. (89 mm)
LCL : 2 17/32 in. (64 mm)

S14

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Filament type	Finish	Case qty (inner/master)
A19									
10161	40A19/CL/20M/120V/STD	40	E26	120	200	20 000	C-9/4	Clear	6/24
A21									
10327 ¹	100A21/F/20M/120V/STD	100	E26	120	800	20 000	C-9/5	Frost	6/24
G25									
14600	40G25/WH/20M/120V	40	E26	120	320	20 000	C-11	White	1/60
G40									
14606	25G40/CL/20M/120V	25	E26	120	190	20 000	C-11	Clear	1/24
R20									
10256 ¹	50R20/SP/20M/120V/STD	50	E26	120	400	20 000	C-9/5	Clear	6/200
S14									
10259	10S14/CL/20M/120V/STD	10	E26	120	50	20 000	C-9/5	Clear	6/24

¹ This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.

Low Voltage




A19



A21



S11



S14

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Filament type	Finish/ Color	Case qty (inner/master)
A19									
52022	25A19/F/1.5M/12V/STD/6P	25	E26	12	220	1 500	C-6	Frost	6/120
69791	25A19/F/1.5M/24V/STD/6P	25	E26	24	280	1 500	C-6	Frost	6/120
52222	25A19/F/1.5M/32V/STD/6P	25	E26	32	220	1 500	C-6	Frost	6/120
52010	50A19/F/1.5M/12V/STD	50	E26	12	410	1 500	C-6	Frost	6/120
69709	50A19/F/2M/24V/STD	50	E26	24	560	2 000	C-6	Frost	6/24
69789	50A19/F/2M/32V/STD/6P	50	E26	32	410	1 500	C-6	Frost	6/120
59846	50A19/F/RS/1M/75V/STD	50	E26	75	500	1 000	C-9	Frost	6/120
70189	100A19/F/2M/24V/STD/6P	100	E26	24	1 350	2 000	C-6	Frost	6/120
52026	100A19/F/1.5M/32V/STD/6P	100	E26	32	1 385	1 500	C-6	Frost	6/120
52225	100A19/F/1.5M/34V/STD/6P	100	E26	34	1 385	1 500	C-6	Frost	6/120
A21									
50075	50A21/F/2M/47V/STD	50	E26	47	650	2 000	C-6	Frost	24/120
S11									
50790	15S11/CL/1M/BA15d/75V/STD	15	BA15d	75	140	1 000	C-7A	Clear	25/500
50791	30S11/CL/BA15d/75V/STD	30	BA15d	75	280	1 000	C-7A	Clear	25/500
S14									
52209	11S14/CL/1.5M/24V/STD	11	E26	24	74	1 500	C-6	Clear	25/500

Rough Service



MOL : 4 1/4 in. (108 mm)
LCL : 3 1/32 in. (77 mm)

A19



MOL : 5 5/16 in. (135 mm)
LCL : 3 17/32 in. (90 mm)

A21



MOL : 6 3/16 in. (157 mm)
LCL : 5 1/32 in. (128 mm)

A23

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Filament type	Finish	Case qty (inner/master)
A19 - 2 pack									
61799	50A19/F/RS/130V/STD/2P	50	E26	130	360	5 000	C-7A	Frost	1/120
61800	60A19/F/RS/130V/STD/2P	60	E26	130	520	5 000	C-7A	Frost	1/120
61801	75A19/F/RS/130V/STD/2P	75	E26	130	680	5 000	C-7A	Frost	1/120
61802	100A19/F/RS/130V/STD/2P	100	E26	130	1 050	5 000	C-7A	Frost	1/120
A21									
52134	100A21/F/RS/130V/STD	100	E26	130	1 050	5 000	C-7A	Frost	6/60
50073	150A21/F/RS/130V/STD	150	E26	130	1 750	5 000	C-7A	Frost	6/60
A23									
50087	150A23/F/RS/130V/STD	150	E26	130	1 750	5 000	C-7A	Frost	6/60
50074	200A23/F/RS/130V/STD	200	E26	130	2 500	5 000	C-7A	Frost	6/60

High Voltage



MOL : 3 1/2 in. (89 mm)
LCL : 2 3/8 in. (60 mm)

A15



MOL : 4 1/4 in. (108 mm)
LCL : 3 1/8 in. (79 mm)

A19



MOL : 3 29/32 in. (99 mm)
LCL : 2 9/16 in. (65 mm)

B10



MOL : 2 5/16 in. (59 mm)
LCL : 1 15/32 in. (37 mm)

T7



MOL : 9 13/32 in. (239 mm)
LCL : 7 in. (178 mm)

PS35

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Filament type	Finish	Case qty (inner/master)
A15									
14797	40A15/IF/250V	40	E26	250	300	5 000	C-9	Frost	1/50
A19									
52021	50A19/F/2M/E27/230 250V/STD	50	E27	230	485	2 000	CC-9	Frost	6/120
B10									
52158	25B10/CL/3M/E12/220V/STD	25	E12	220	185	3 000	C-7A	Clear	25/500
T7									
52193	15T7/CL/1.5M/E12/250V/STD	15	E12	250	95	1 500	C-7A	Clear	25/1 000
PS35									
14660	500PS35/CL/2M/E39/240V	500	E39	240	8 500	2 000	CC-9	Clear	1/12