

Project:		Type:	
Drawn by:	Catalogue #:	Date:	
Diami by:	outuioguo ii :	Batt.	

Individual Spec Sheet

FIXTURE CONTROLLER 120-347 V

FIELD INSTALLABLE

Integrated Bluetooth® Mesh Technology

ORDERING INFORMATION

Order Code: 70245

Model Number: CTRL-KBPQ-002 UPC: 069549033122 DLC ID: N-HK2HBX

This 120-347 V AC Fixture Controller enables seamless conversion of luminaires to wireless control for integration within the Genio system. Paired with motion sensors, the device settings and commissioning are configured through our Genio app via a smart phone.

TECHNICAL SPECS

Input Voltage: 120-347 V AC Frequency: 50/60 Hz **Output Voltage:** 120-347 V AC **Output Current:** 6 A Max

Output Power: 720 W Max @ 120 V, 1 662 W Max @ 277 V, 2 082 W Max @ 347 V

Dimming: Class 2, 0-10 V DC 10 mA Max


Sinking Current: 10 mA Max Color: White

Operating Temperature: -30 °C to 65 °C (-22 °F to 149 °F) Storage temperature: -30 °C to 85 °C (-22 °F to 185 °F)

Housing Material: UL 94-5 VA Bluetooth® Transmit: 200 ft Max **Radio Frequency:** $2.4~\mathrm{GHz}\pm75~\mathrm{MHz}$

IP Rating: IP20

DIMENSIONS



1/2 inch US standard knockout

Socket Mounting Dimensions			
Size	T.P.I	Major Dia.	
	inch	inch	
R1/2	14	0.825	



Bluetooth°











indoor



This lighting equipment meets requirements of ICES-005 issue 5 class B for use in residential applications Data is based upon tests performed in a controlled environment.


Actual performance can vary depending on operating conditions. Specifications are subject to change without notice







WIRING



Qty	Description	Price		
I accept the specifications of the luminaire configuration mentioned above. Name:				
Company: Signature:				
Signature:		Date:		

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice. Please contact your Stanpro customer service representative to confirm inventory levels at time of order.







GENIO CONTROL SYSTEM FEATURES

Genio is Stanpro's smart brand of lighting and emergency lighting. Integrating the latest in Bluetooth® Mesh technology, Genio products allow for customizable features that can be adjusted at your fingertips using a smartphone or other compatible devices. This system is easy to use, versatile and futureproof! Please see below for some of the key features¹ of the Genio control system:



LIGHTS

Instantly control the color temperature, wattage, lumen output and dimming.



GROUPS

Easily group luminaires together and control them as a single unit.



SCENES

Customize your lighting through scenes and create different atmospheres for occasions and activities.



SCHEDULES

Set schedules to specify dates, times and recurrence patterns for changing the settings of your lighting.



SENSOR

Adjust the integrated PIR motion sensor and daylight harvesting settings.



Lights

- Add
- Name or Rename
- Dimming and Color Tuning
- Delete
- Sensor Settings



Groups

- Create
- Rename
- Delete
- Add or Remove Lights
- Adjust Group Linkage Level
- Turn On/Off
- Adjust Group Dimming
- Activate Auto Mode



Scenes

- Create
- Edit
- Delete



Schedules

- Creating
- Associate a Schedule To Lights, Groups, or Scenes
- Set a Repeating
- Set Fade Time
- Delete
- Enable Or Disable





Download on the App Store





Download our App Instruction Guide

The Bluetooth® word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Ascot Capital Group is under license. Other trademarks and trade names are those of their respective owners.



¹ Please note that the features mentioned are part of a broader range of characteristics relating to the Genio Ecosystem and may not be applicable to this specific product. Customers are advised to review the product specifications carefully to understand their capabilities.